

AGQ20T03 Information

Heisener.com

Part Number AGQ20T03

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 3V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGQ20T03 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage Contact Form Contact Rating (Current) Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Relays Relays Signal Relays, Up to 2 Amps Fanasonic Electric Works Relays Panasonic Electric Works Relays Panasonic Electric Works Fanasonic Electric Works Panasonic Electric Works Signal Relays Lectrony Signal Relays Lectrony AGQ TH Relays General Purpose Non Latching 46.7mA 3 VDC DPDT (2 Form C) 2 A Switching Voltage 125VAC, 110VDC - Max 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time	•	
Category Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125 VAC, 110 VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms	Manufacturer Part Number	AGQ20T03
Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Manufacturer	Panasonic Electric Works
Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Category	Relays
Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms		Signal Relays, Up to 2 Amps
Relay Type Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms	Package	-
Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Series	AGQ TH
Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Relay Type	General Purpose
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Coil Current	46.7mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms	Coil Voltage	3VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 0.3 VDC 4ms	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms	Turn On Voltage (Max)	2.25 VDC
	Turn Off Voltage (Min)	0.3 VDC
Release Time 4ms	Operate Time	4ms
	Release Time	4ms
Features 3.5A Inrush	Features	3.5A Inrush
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

AGQ20T03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGQ20T03 Payment Methods





















AGQ20T03 Shipping Methods













If you have any question about AGQ20T03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com