

AGQ20T03 Information

Heisener.com

Part Number AGQ20T03

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 3V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGQ20T03 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 4ms Release Time 4ms Mounting Type Through Hole Termination Style Papert agrees?		
CategoryRelaysPackage-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	AGQ20T03
Package Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Manufacturer	Panasonic Electric Works
Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesAGQ THRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Series	AGQ TH
Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Coil Current	46.7mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Coil Voltage	3VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Ams Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style 2.25 VDC 4ms 4ms Features PC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style O.3 VDC 4ms 4ms PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	2.25 VDC
Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.3 VDC
Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	3.5A Inrush
·	Mounting Type	Through Hole
Papart arrars?	Termination Style	PC Pin
Report errors?		Report errors?

AGQ20T03 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGQ20T03 Payment Methods





















AGQ20T03 Shipping Methods













If you have any question about AGQ20T03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com