



AGQ20T1H Information

Heisener.com

Part Number AGQ20T1H

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 1.5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGQ20T1H Specifications

Manufacturer Part Number AGQ20T1H Manufacturer Panasonic Electric Works Category Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Non Latching Coil Current 93.8mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage1.25VAC, 110VDC - MaxTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Manufacturer Part Number	AGQ20T1H
Package-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage1.25VAC, 110VDC - MaxTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Manufacturer	Panasonic Electric Works
Package-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage1.25VAC, 110VDC - MaxTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Category	Relays
SeriesAGQ THRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current93.8mACoil Voltage1.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)1.13 VDCTurn Off Voltage (Min)0.15 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 93.8mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Series	AGQ TH
Coil Current 93.8mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Coil Type	Non Latching
Contact Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Coil Current	93.8mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Coil Voltage	1.5VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) 0.15 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 1.13 VDC Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Switching Voltage	125VAC, 110VDC - Max
Operate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Turn On Voltage (Max)	1.13 VDC
Release Time4msFeatures3.5A InrushMounting TypeThrough Hole	Turn Off Voltage (Min)	0.15 VDC
Features 3.5A Inrush Mounting Type Through Hole	Operate Time	4ms
Mounting Type Through Hole	Release Time	4ms
	Features	3.5A Inrush
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

AGQ20T1H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGQ20T1H Payment Methods

































If you have any question about AGQ20T1H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com