

# **AGQ21024 Information**



For Reference Only

Part Number AGQ21024

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY TELECOM DPDT 2A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **AGQ21024 Specifications**

Manufacturer Part Number  Manufacturer  Panasonic Electric Works  Relays  Signal Relays, Up to 2 Amps  Package		
CategoryRelaysPackage-SeriesAGQRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	AGQ21024
Package-SeriesAGQRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series AGQ Relay Type Telecom Coil Type Latching, Single Coil Coil Current 5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesAGQRelay TypeTelecomCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	AGQ
Coil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time4msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Relay Type	Telecom
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Through Hole  Termination Style	Coil Current	5mA
Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) - Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Through Hole  Termination Style  18 VDC  -  4ms  Through Hole  PC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  -  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	18 VDC
Release Time 4ms  Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### **AGQ21024 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **AGQ21024 Payment Methods**





















### **AGQ21024 Shipping Methods**













If you have any question about AGQ21024, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com