



AGQ21T12 Information

Heisener.com

Part Number AGQ21T12

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGQ21T12 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style		
CategoryRelaysPackage-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	AGQ21T12
Package-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 8.3mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Category	Relays
SeriesAGQ THRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Single CoilCoil Current8.3mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin	Series	AGQ TH
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style 9 VDC 4ms 4ms 4ms PC Pin	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style 1.2 VDC 4ms 4ms PC Pin	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9 VDC
Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features 3.5A Inrush Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	3.5A Inrush
	Mounting Type	Through Hole
D	Termination Style	PC Pin
Report errors?		Report errors?

AGQ21T12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGQ21T12 Payment Methods



















AGQ21T12 Shipping Methods













If you have any question about AGQ21T12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com