

# **AGQ21T24 Information**

Heisener.com

Part Number AGQ21T24

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 2A 24V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **AGQ21T24 Specifications**

Manufacturer Part NumberAGQ21T24ManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesAGQ THRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Manufacturer Part Number	AGQ21T24
Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Mounting Type Through Hole	Manufacturer	Panasonic Electric Works
Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Turnout Hores AGQ TH Release Time 4mrouse AGQ TH Release Time 5.5A Inrush Through Hole	Category	Relays
SeriesAGQ THRelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay Type Coil Type Latching, Single Coil Coil Current 5mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Mounting Type Through Hole	Package	-
Coil TypeLatching, Single CoilCoil Current5mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 110VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeatures3.5A InrushMounting TypeThrough Hole	Series	AGQ TH
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  4ms  Release Time  4ms  Features  3.5A Inrush  Mounting Type  Through Hole	Coil Current	5mA
Contact Rating (Current)  Switching Voltage  125VAC, 110VDC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  4ms  Release Time  4ms  Features  3.5A Inrush  Mounting Type  Through Hole	Coil Voltage	24VDC
Switching Voltage 125VAC, 110VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  3.5A Inrush  Mounting Type  Through Hole	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  4ms  Release Time  4ms  Features  3.5A Inrush  Mounting Type  Through Hole	Switching Voltage	125VAC, 110VDC - Max
Operate Time 4ms Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Turn On Voltage (Max)	18 VDC
Release Time 4ms Features 3.5A Inrush Mounting Type Through Hole	Turn Off Voltage (Min)	2.4 VDC
Features 3.5A Inrush Mounting Type Through Hole	Operate Time	4ms
Mounting Type Through Hole	Release Time	4ms
	Features	3.5A Inrush
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

### **AGQ21T24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **AGQ21T24 Payment Methods**



















### **AGQ21T24 Shipping Methods**













If you have any question about AGQ21T24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com