



AGQ21TS4HZ Information

Heisener.com

Part Number AGQ21TS4HZ

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AGQ21TS4HZ Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage Turn On Voltage (Max) AGQ TH Panasonic Electric Works Relays Signal Relays, Up to 2 Amps - Camps - Camps AGQ TH General Purpose Latching, Single Coil 22.2mA 4.5VDC DPDT (2 Form C) 2A Switching Voltage 125VAC, 110VDC - Max 3.38 VDC	
Category Relays Signal Relays, Up to 2 Amps Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max	
Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max	
Package - Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max	
Series AGQ TH Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max	
Relay Type Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 110VDC - Max	
Coil Type Latching, Single Coil Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max	
Coil Current 22.2mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max	
Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max	
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 110VDC - Max	
Contact Rating (Current) Switching Voltage 2A 125VAC, 110VDC - Max	
Switching Voltage 125VAC, 110VDC - Max	
Turn On Voltage (May)	
Turn On Voltage (Max) 3.38 VDC	
Turn Off Voltage (Min) 0.45 VDC	
Operate Time 4ms	
Release Time 4ms	
Features 3.5A Inrush	
Mounting Type Surface Mount	
Termination Style Gull Wing	
Report er	ors?

AGQ21TS4HZ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AGQ21TS4HZ Payment Methods





















AGQ21TS4HZ Shipping Methods













If you have any question about AGQ21TS4HZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com