



AHM100PS48 Information



For Reference Only

Part Number AHM100PS48
Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 48V 100W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AHM100PS48 Specifications

Manufacturer Part Number AHM100PS48 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AHM Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AHM Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Manufacturer Part Number	AHM100PS48
AC DC Desktop, Wall Adapters Package Series AHM Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension AHM AHM AMM AHM AHM AHM AHM AHM AHM AH	Manufacturer	XP Power
Package - Series AHM Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesAHMRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.29^{\circ}\text{L} \times 2.52^{\circ}\text{W} \times 1.45^{\circ}\text{H} (160.0 \text{mm} \times 64.0 \text{mm} \times 37.0 \text{mm})$		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output48VCurrent - Output (Max)2.08APower (Watts)100WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Series	AHM
Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Region Utilized	International
Voltage - Input80 ~ 264 VACVoltage - Output48VCurrent - Output (Max)2.08APower (Watts)100WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial), MedicalEfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Form	Desktop (Class I)
Voltage - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.08A Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 2.08A 2.08A 2.08 2.08 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Voltage - Input	80 ~ 264 VAC
Power (Watts) 100W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Voltage - Output	48V
No Load Power Consumption 500mW (Max) Polarization - ITE (Commercial), Medical Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 6.29° L x 2.52° W x 1.45° H (160.0 mm x 64.0 mm x 37.0 mm)	Current - Output (Max)	2.08A
Polarization - Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Power (Watts)	100W
Applications ITE (Commercial), Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.29^{\circ}\text{L} \times 2.52^{\circ}\text{W} \times 1.45^{\circ}\text{H} (160.0 \text{mm} \times 64.0 \text{mm} \times 37.0 \text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.29^{\circ}\text{L x } 2.52^{\circ}\text{W x } 1.45^{\circ}\text{H } (160.0\text{mm x } 64.0\text{mm x } 37.0\text{mm})$	Polarization	-
Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Applications	ITE (Commercial), Medical
Output Connector Power DIN, 4 Pin Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Efficiency	Level V
Size / Dimension 6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.29" L x 2.52" W x 1.45" H (160.0mm x 64.0mm x 37.0mm)
T		Report errors?

AHM100PS48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AHM100PS48 Payment Methods





















AHM100PS48 Shipping Methods













If you have any question about AHM100PS48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com