

AHN22048 Information



For Reference Only

Part Number AHN22048

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AHN22048 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series AHN Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Mounting Type Socketable Plug In		
CategoryRelaysPackage-SeriesAHNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time5msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	AHN22048
Package - Series AHN Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Purpose	Manufacturer	Panasonic Electric Works
Package - Series AHN Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesAHNRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time5msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current11mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time5msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	AHN
Coil Current 11mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	11mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style	Coil Voltage	48VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 30VDC - Max
Operate Time 15ms Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	33.6 VDC
Release Time 5ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	4.8 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	5ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
Tepott offolis.		Report errors?

AHN22048 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AHN22048 Payment Methods


































If you have any question about AHN22048, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com