



AK1601-9PG Information

Heisener.com

Part Number AK1601-9PG

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERTER

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AK1601-9PG Specifications

Manufacturer Part Number AK1601-9PG Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series Melcher K Type Front End Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm) Report errors?			
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package - Series Melcher K Type Front End Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Manufacturer Part Number	AK1601-9PG	
Package - Series Melcher K Type Front End Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Manufacturer	Bel Power Solutions	
Package - Series Melcher K Type Front End Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series Melcher K Type Front End Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)		DC DC Converters	
Type Front End Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Package	-	
Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Series	Melcher K	
Voltage - Input (Max) 35V Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Type	Front End	
Number of Outputs 1 Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Voltage - Input (Min)	8V	
Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 120W Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Voltage - Input (Max)	35V	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case Size / Dimension - Current - Output (Max) 5A - Commercial), Railway - Chassis Mount 1TE (Commercial), Railway - Commercial), Railway	Number of Outputs	1	
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Size / Dimension	Voltage - Output 1	24V	
Voltage - Output 4 Current - Output (Max) 5A Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case Size / Dimension	Voltage - Output 2	-	
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case Size / Dimension 5A 120W Commercial), Railway -40°C ~ 71°C Chassis Mount 14.5% Chassis Mount 15.5% Chassis Mount 16.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case Size / Dimension 120W Commercial), Railway -40°C ~ 71°C Chasilway -40°C ~ 71°C Silway -40°C ~ 71°C Silway -40°C ~ 71°C -40°C ~ 7	Voltage - Output 4	-	
Applications ITE (Commercial), Railway Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Current - Output (Max)	5A	
Operating Temperature -40°C ~ 71°C Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Power (Watts)	120W	
Efficiency 84.5% Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Applications	ITE (Commercial), Railway	
Mounting Type Chassis Mount Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Operating Temperature	-40°C ~ 71°C	
Package / Case - Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Efficiency	84.5%	
Size / Dimension 6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	Mounting Type	Chassis Mount	
	Package / Case	-	
Report errors?	Size / Dimension	6.60" L x 4.40" W x 3.20" H (167.6mm x 111.8mm x 81.3mm)	
		Report errors	?

AK1601-9PG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AK1601-9PG Payment Methods



















AK1601-9PG Shipping Methods













If you have any question about AK1601-9PG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com