

AK2320-7R Information

Heisener.com

Part Number AK2320-7R

Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description DC/DC CONVERT DUAL 12V 5A

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AK2320-7R Specifications

| Manufacturer Part Number AK2320-7R Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher K Type Isolated Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) Report errors? | | | |
|--|--------------------------|--|----|
| Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series Melcher K Type Isolated Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Manufacturer Part Number | AK2320-7R | |
| Package Module Series Melcher K Type Isolated Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Manufacturer | Bel Power Solutions | |
| Package Module Series Melcher K Type Isolated Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Category | Power Supplies - External/Internal (Off-Board) | |
| Series Melcher K Type Isolated Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | | DC DC Converters | |
| Type Isolated Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Package | Module | |
| Voltage - Input (Min) 8V Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Series | Melcher K | |
| Voltage - Input (Max) 35V Number of Outputs 2 Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Type | Isolated | |
| Number of Outputs2Voltage - Output 112VVoltage - Output 212VVoltage - Output 3-Voltage - Output 4-Current - Output (Max)5A, 5APower (Watts)150WApplicationsITE (Commercial), RailwayOperating Temperature-25°C ~ 71°CEfficiency78%Mounting TypeChassis MountPackage / CaseModuleSize / Dimension6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Voltage - Input (Min) | 8V | |
| Voltage - Output 1 12V Voltage - Output 2 12V Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Voltage - Input (Max) | 35V | |
| Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension 12V 12V 12V 12V 12V 12V 12V 12 | Number of Outputs | 2 | |
| Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Operating Temperature Efficiency Mounting Type Chassis Mount Package / Case Module Size / Dimension Size / Dimension Size / Output 4 | Voltage - Output 1 | 12V | |
| Voltage - Output 4 Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension -25°C ~ 31°C Chassis Mount Mounting Type Chassis Mount Mounting Type 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Voltage - Output 2 | 12V | |
| Current - Output (Max) 5A, 5A Power (Watts) 150W Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Voltage - Output 3 | - | |
| Power (Watts) Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 150W ITE (Commercial), Railway -25°C ~ 71°C Chasilway -25°C ~ 71°C Nounting Type Chassis Mount 178% 189% | Voltage - Output 4 | - | |
| Applications ITE (Commercial), Railway Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Current - Output (Max) | 5A, 5A | |
| Operating Temperature -25°C ~ 71°C Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Power (Watts) | 150W | |
| Efficiency 78% Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Applications | ITE (Commercial), Railway | |
| Mounting Type Chassis Mount Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Operating Temperature | -25°C ~ 71°C | |
| Package / Case Module Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Efficiency | 78% | |
| Size / Dimension 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | Mounting Type | Chassis Mount | |
| | Package / Case | Module | |
| Report errors? | Size / Dimension | 6.73" L x 4.37" W x 3.15" H (171.0mm x 111.0mm x 80.0mm) | |
| | | Report error | s? |

AK2320-7R Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AK2320-7R Payment Methods


































If you have any question about AK2320-7R, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com