

ALA2PF24 Information



For Reference Only

Part Number ALA2PF24

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALA2PF24 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series ALA Relay Type General Purpose Coil Current 22.1mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	ALA2PF24
Package - Series ALA Relay Type General Purpose Coil Type Non Latching Coil Current 22.1mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style Purpose	Manufacturer	Panasonic Electric Works
Package-SeriesALARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesALARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	ALA
Coil Current 22.1mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	22.1mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 5A 277VAC - Max 18 VDC 15ms 15ms Peatures Peatures Sealed - Flux Protection Through Hole PC Pin	Coil Voltage	24VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	277VAC - Max
Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	18 VDC
Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	15ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

ALA2PF24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALA2PF24 Payment Methods





















ALA2PF24 Shipping Methods













If you have any question about ALA2PF24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com