

ALA2PF24 Information



For Reference Only

Part Number ALA2PF24

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALA2PF24 Specifications

| Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series ALA Relay Type General Purpose Coil Current 22.1mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole PC Pin | | |
|--|--------------------------|---------------------------|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin | Manufacturer Part Number | ALA2PF24 |
| Package - Series ALA Relay Type General Purpose Coil Type Non Latching Coil Current 22.1mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style Purpose | Manufacturer | Panasonic Electric Works |
| Package-SeriesALARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin | Category | Relays |
| SeriesALARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin | | Power Relays, Over 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin | Package | - |
| Coil TypeNon LatchingCoil Current22.1mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)5ASwitching Voltage277VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin | Series | ALA |
| Coil Current 22.1mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Relay Type | General Purpose |
| Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Coil Type | Non Latching |
| Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Coil Current | 22.1mA |
| Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 5A 277VAC - Max 18 VDC 15ms 15ms Peatures Peatures Sealed - Flux Protection Through Hole PC Pin | Coil Voltage | 24VDC |
| Switching Voltage 277VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Contact Form | DPST (2 Form A) |
| Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Contact Rating (Current) | 5A |
| Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Switching Voltage | 277VAC - Max |
| Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin | Turn On Voltage (Max) | 18 VDC |
| Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 1.2 VDC |
| Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin | Operate Time | 15ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 15ms |
| Termination Style PC Pin | Features | Sealed - Flux Protection |
| | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

ALA2PF24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALA2PF24 Payment Methods





















ALA2PF24 Shipping Methods













If you have any question about ALA2PF24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com