

ALC10A471DL550

Request a Quote

ALC10A471DL550 Information

www.heisener.com	Part Number	ALC10A471DL550
	Manufacturer	KEMET
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 470UF 20% 550V SNAP-IN
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact us
r Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ALC10A471DL550 Specifications

Manufacturer Part NumberALC10A471DL550ManufacturerKEMETCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesALC10Capacitance470µFTolerance±20%Voltage - Rated550 VESR (Equivalent Series Resistance)500 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizon2000 Hrs @ 85°COplariting Temperature2003 General PurposeApplicationsGeneral PurposeRipple Current - Low Frequency851 MolMaLipedance650 mOhmsLada Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension-Mounting TypeThrough HolePackage / Case-Mounting TypeThrough HolePackage / Case-	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series ALC10 Capacitance 470µF Tolerance ±20% Voltage - Rated 550V ESR (Equivalent Series Resistance) 746 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 287A @ 100Hz Impedance 650 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size - Mounting Type Finought Hole	Manufacturer Part Number	ALC10A471DL550
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesALC10Capacitance470µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)746 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsSerieral PurposeRipple Current - Low Frequency2.87A @ 100HzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension3.228" (82.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Manufacturer	KEMET
PackageRadial, Can - Snap-InSeriesALC10Capacitance470µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)746 mOhm @ 100HzOperating Temperature2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency2.87A @ 100HzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension3.228" (82.00mn)Hight - Seated (Max)3.228" (82.00mn)Surface Mount Land Size-Hourting TypeHrough HolePackage / CaseKadia, Can - Snap-In	Category	Capacitors
SeriesALC10Capacitance470µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)746 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature440°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzImpedance650 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)746 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzImpedance650 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated550VESR (Equivalent Series Resistance)746 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	ALC10
Voltage - Rated550VESR (Equivalent Series Resistance)746 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzImpedance650 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can - Snap-In	Capacitance	470µF
FSR (Equivalent Series Resistance)746 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	550V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	746 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.87A @ 100HzRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.87A @ 100HzRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
InInRipple Current - High Frequency4.43A @ 10kHzImpedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance650 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.87A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	4.43A @ 10kHz
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	650 mOhms
Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	3.228" (82.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
Report on		Report errors?

ALC10A471DL550 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ALC10A471DL550 Payment Methods



ALC10A471DL550 Shipping Methods



If you have any question about ALC10A471DL550, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com