



## **ALC40A471DE400 Information**



For Reference Only

Part Number ALC40A471DE400

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 470UF 20% 400V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ALC40A471DE400 Specifications**

Manufacturer Part Number         ALC40A471DE400           Manufacturer         KEMET           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         ALC40           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5 & @ 100Hz           Ripple Current - High Frequency         4.73A @ 10kHz           Impedance         192 m0hms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.772" (45.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	•	
Category         Capacitors           Package         Radial, Can - Snap-In           Series         ALC40           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         4.73A @ 10kHz           Impedance         192 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.772" (45.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	ALC40A471DE400
Package         Radial, Can - Snap-In           Series         ALC40           Capacitance         470µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         4.73A @ 10kHz           Impedance         192 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.772" (45.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer	KEMET
Package         Radial, Can - Snap-In           Series         ALC40           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         4.73A @ 10kHz           Impedance         192 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.772" (45.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         ALC40           Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         4.73A @ 10kHz           Impedance         192 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.772" (45.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance         470μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         4.73A @ 10kHz           Impedance         192 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.772" (45.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose Ripple Current - Low Frequency 2.5A @ 100Hz  Ripple Current - High Frequency 4.73A @ 10kHz  Impedance 192 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.772" (45.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	ALC40
Voltage - Rated400 VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency4.73A @ 10kHzImpedance192 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.772" (45.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	470μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.5A @ 100Hz  Ripple Current - High Frequency  4.73A @ 10kHz  Impedance  192 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.772" (45.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.5A @ 100Hz Ripple Current - High Frequency 4.73A @ 10kHz Impedance 192 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.772" (45.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.5A @ 100Hz  Ripple Current - High Frequency 4.73A @ 10kHz  Impedance 192 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.772" (45.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Applications General Purpose Ripple Current - Low Frequency 2.5A @ 100Hz Ripple Current - High Frequency 4.73A @ 10kHz Impedance 192 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.772" (45.00mm) Surface Mount Land Size  Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 2.5A @ 100Hz Ripple Current - High Frequency 4.73A @ 10kHz Impedance 192 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.772" (45.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  4.73A @ 10kHz  Impedance  192 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.772" (45.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency  4.73A @ 10kHz  Impedance  192 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.772" (45.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Applications	General Purpose
Impedance192 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.772" (45.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.5A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.772" (45.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	4.73A @ 10kHz
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.772" (45.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	192 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.772" (45.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

### **ALC40A471DE400 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ALC40A471DE400 Payment Methods**



















# **ALC40A471DE400 Shipping Methods**













If you have any question about ALC40A471DE400, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com