



### **ALE14B12 Information**



For Reference Only

Part Number ALE14B12

Manufacturer Panasonic Electric Works

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 16A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ALE14B12 Specifications**

Manufacturer Part NumberALE14B12ManufacturerPanasonic Electric WorksCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	ALE14B12
Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer	Panasonic Electric Works
Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class B Mounting Type Through Hole Termination Style Perpose 1.50	Category	Relays
SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)0.6 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class BMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Package	-
Coil Type Non Latching Coil Current 33.3mA  Coil Voltage 12VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 277VAC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 20ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Through Hole  Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Series	ALE
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 12VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 277VAC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 20ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Through Hole  Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 277VAC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 20ms  Release Time 20ms  Release Time 1 Insulation - Class B  Mounting Type Through Hole  Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Current	33.3mA
Contact Rating (Current)  Switching Voltage  277VAC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  20ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Through Hole  Termination Style  PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Voltage	12VDC
Switching Voltage 277VAC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 20ms  Release Time 20ms  Features Insulation - Class B  Mounting Type Through Hole  Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  20ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Through Hole  Termination Style  PC Pin, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  Insulation - Class B  Mounting Type  Through Hole  Termination Style  PC Pin, Quick Connect - 0.187" (4.7mm)	Switching Voltage	277VAC - Max
Operate Time 20ms Release Time 20ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	9 VDC
Release Time 20ms Features Insulation - Class B Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class B  Mounting Type Through Hole  Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Release Time	20ms
Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Features	Insulation - Class B
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.187" (4.7mm)
		Report errors?

#### **ALE14B12 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ALE14B12 Payment Methods**





















### **ALE14B12 Shipping Methods**













If you have any question about ALE14B12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com