



ALE14F48 Information



For Reference Only

Part Number ALE14F48

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALE14F48 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series ALE Relay Type General Purpose Coil Current 8.3mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Release Time Features Mounting Type Through Hole PC Pin, Quick Connect - 0.187" (4.7mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	ALE14F48
Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer	Panasonic Electric Works
Package - Series ALE Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesALERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Release Time 1 Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Package	-
Coil TypeNon LatchingCoil Current8.3mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Series	ALE
Coil Current8.3mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage277VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20msRelease Time20msFeaturesInsulation - Class FMounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Release Time 1 Insulation - Class F Mounting Type 1 Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Voltage	48VDC
Switching Voltage 277VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style 36 VDC 1.4 VDC 2.4 VDC 20ms 20ms 4.7 Mounting Type Through Hole PC Pin, Quick Connect - 0.187" (4.7 mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Switching Voltage	277VAC - Max
Operate Time 20ms Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	36 VDC
Release Time 20ms Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	2.4 VDC
Features Insulation - Class F Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Release Time	20ms
Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Features	Insulation - Class F
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.187" (4.7mm)
		Report errors?

ALE14F48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALE14F48 Payment Methods





















ALE14F48 Shipping Methods













If you have any question about ALE14F48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com