



ALM65US24C2-8 Information

Part Number ALM65US24C2-8

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 65W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALM65US24C2-8 Specifications

Manufacturer Part Number ALM65US24C2-8 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ALM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ALM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Manufacturer Part Number	ALM65US24C2-8
Package - Series ALM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Manufacturer	XP Power
Package - Series ALM Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesALMRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.7APower (Watts)65WNo Load Power Consumption210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm x 33.5mm)Size / Dimension4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm \times 9.5.5mm \times 33.5mm) Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Series	ALM
Input TypeCord (Sold Separately)Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension $4.94^{\circ}\text{L} \times 2.19^{\circ}\text{W} \times 1.32^{\circ}\text{H}$ (125.5mm $\times 55.5\text{mm} \times 33.5\text{mm}$)	Region Utilized	International
Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm x 33.5mm)Size / Dimension 4.94° L x 2.19° W x 1.32° H (125.5mm x 55.5mm x 33.5mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 2.7A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial), Medical Efficiency Operating Temperature O°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.7A Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Voltage - Input	80 ~ 264 VAC
Power (Watts) 65W No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Voltage - Output	24V
No Load Power Consumption 210mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Current - Output (Max)	2.7A
Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.94^{\circ}\text{L} \times 2.19^{\circ}\text{W} \times 1.32^{\circ}\text{H} (125.5\text{mm} \times 55.5\text{mm} \times 33.5\text{mm})$	Power (Watts)	65W
Applications ITE (Commercial), Medical Efficiency Level VI Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94° L x 2.19° W x 1.32° H (125.5 mm x 33.5 mm)	No Load Power Consumption	210mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.94^{\circ}\text{L} \times 2.19^{\circ}\text{W} \times 1.32^{\circ}\text{H} (125.5\text{mm} \times 55.5\text{mm} \times 33.5\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.94^{\circ}\text{L} \times 2.19^{\circ}\text{W} \times 1.32^{\circ}\text{H} (125.5\text{mm} \times 55.5\text{mm} \times 33.5\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Efficiency	Level VI
Size / Dimension 4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.94" L x 2.19" W x 1.32" H (125.5mm x 55.5mm x 33.5mm)
		Report errors?

ALM65US24C2-8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALM65US24C2-8 Payment Methods





















ALM65US24C2-8 Shipping Methods













If you have any question about ALM65US24C2-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com