



### **ALM85US19C2-8 Information**

Part Number ALM85US19C2-8

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 19V 85W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ALM85US19C2-8 Specifications**

Manufacturer Part Number         ALM85US19C2-8           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         ALM85           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         80 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         4.47A           Power (Watts)         85W           No Load Power Consumption         150mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial), Medical           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)    Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         ALM85           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         80 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         4.47A           Power (Watts)         85W           No Load Power Consumption         150mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial), Medical           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Manufacturer Part Number	ALM85US19C2-8
Package         -           Series         ALM85           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         80 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         4.47A           Power (Watts)         85W           No Load Power Consumption         150mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial), Medical           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Manufacturer	XP Power
Package         -           Series         ALM85           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord (Sold Separately)           Voltage - Input         80 ~ 264 VAC           Voltage - Output         19V           Current - Output (Max)         4.47A           Power (Watts)         85W           No Load Power Consumption         150mW (Max)           Polarization         Positive Center           Applications         ITE (Commercial), Medical           Efficiency         Level VI, CoC Tier 2           Operating Temperature         0°C ~ 60°C           Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesALM85Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output19VCurrent - Output (Max)4.47APower (Watts)85WNo Load Power Consumption150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America  Form Desktop (Class II)  Input Type Cord (Sold Separately)  Voltage - Input 80 ~ 264 VAC  Voltage - Output 19V  Current - Output (Max) 4.47A  Power (Watts) 85W  No Load Power Consumption 150mW (Max)  Polarization Positive Center  Applications ITE (Commercial), Medical  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 60°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately)  Voltage - Input 80 ~ 264 VAC  Voltage - Output 19V  Current - Output (Max) 4.47A  Power (Watts) 85W  No Load Power Consumption 150mW (Max)  Polarization Positive Center  Applications ITE (Commercial), Medical  Efficiency Level VI, CoC Tier 2  Operating Temperature 0°C ~ 60°C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Series	ALM85
Input TypeCord (Sold Separately)Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output $19\text{V}$ Current - Output (Max) $4.47\text{A}$ Power (Watts) $85\text{W}$ No Load Power Consumption $150\text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5\text{mm}$ I.D. $\times 5.5\text{mm}$ O.D. $\times 9.5\text{mm}$ Size / Dimension $5.31$ " L $\times 2.44$ " W $\times 1.46$ " H ( $135.0\text{mm} \times 62.0\text{mm} \times 37.0\text{mm}$ )	Region Utilized	North America
Voltage - Input  80 ~ 264 VAC  Voltage - Output  19V  Current - Output (Max)  4.47A  Power (Watts)  85W  No Load Power Consumption  150mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial), Medical  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 60°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Form	Desktop (Class II)
Voltage - Output  Current - Output (Max)  4.47A  Power (Watts)  No Load Power Consumption  Polarization  Polarization  Applications  ITE (Commercial), Medical  Efficiency  Current - Output (Max)  Power (Watts)  Power (Watts)  Positive Center  ITE (Commercial), Medical  Efficiency  Current - Output Connector  Current - Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  Size / Dimension  Size / Dimension	Input Type	Cord (Sold Separately)
Current - Output (Max)  4.47A  Power (Watts)  85W  No Load Power Consumption  150mW (Max)  Polarization  Positive Center  Applications  ITE (Commercial), Medical  Efficiency  Level VI, CoC Tier 2  Operating Temperature  0°C ~ 60°C  Output Connector  Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension  5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Voltage - Input	80 ~ 264 VAC
Power (Watts)85WNo Load Power Consumption $150 \text{mW}$ (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, $2.5 \text{mm}$ I.D. $\times 5.5 \text{mm}$ O.D. $\times 9.5 \text{mm}$ Size / Dimension $5.31$ " L $\times 2.44$ " W $\times 1.46$ " H (135.0 mm $\times 62.0 \text{mm} \times 37.0 \text{mm}$ )	Voltage - Output	19V
No Load Power Consumption 150mW (Max)  Polarization Positive Center  Applications ITE (Commercial), Medical  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Current - Output (Max)	4.47A
Polarization Positive Center  Applications ITE (Commercial), Medical  Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Power (Watts)	85W
Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}$ C $\sim 60^{\circ}$ C  Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	No Load Power Consumption	150mW (Max)
Efficiency Level VI, CoC Tier 2  Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm  Size / Dimension $5.31^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.46^{\circ}\text{H} (135.0 \text{mm} \times 37.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.31^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.46^{\circ}\text{H} (135.0\text{mm} \times 37.0\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector         Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm           Size / Dimension         5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)
		Report errors?

#### **ALM85US19C2-8 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ALM85US19C2-8 Payment Methods**



















## **ALM85US19C2-8 Shipping Methods**













If you have any question about ALM85US19C2-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com