



ALM85US24C2-8 Information

Part Number ALM85US24C2-8

Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 85W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALM85US24C2-8 Specifications

Manufacturer Part Number ALM85US24C2-8 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series ALM85 Region Utilized North America Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ALM85 Region Utilized North America Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Manufacturer Part Number	ALM85US24C2-8
Package-SeriesALM85Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input $80 \sim 264 \text{ VAC}$ Voltage - Output $24V$ Current - Output (Max) $3.54A$ Power (Watts) $85W$ No Load Power Consumption 150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31°L x 2.44°W x 1.46°H (135.0mm x 62.0mm x 37.0mm)	Manufacturer	XP Power
Package - Series ALM85 Region Utilized North America Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesALM85Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input80 ~ 264 VACVoltage - Output24VCurrent - Output (Max)3.54APower (Watts)85WNo Load Power Consumption150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VI, CoC Tier 2Operating Temperature0°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Series	ALM85
Input Type	Region Utilized	North America
Voltage - Input 80 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 3.54A Power (Watts) No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 3.54A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial), Medical Efficiency Current - Output (Max) Power (Watts) Positive Center ITE (Commercial), Medical Efficiency Current - Output Connector Duput Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 3.54A Power (Watts) 85W No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Voltage - Input	80 ~ 264 VAC
Power (Watts) No Load Power Consumption 150mW (Max) Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Voltage - Output	24V
No Load Power Consumption 150mW (Max)PolarizationPositive CenterApplicationsITE (Commercial), MedicalEfficiencyLevel VI, CoC Tier 2Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5 \text{mm}$ O.D. $x 9.5 \text{mm}$ Size / Dimension 5.31 " L $x 2.44$ " W $x 1.46$ " H (135.0 mm $x 62.0 \text{mm}$ $x 37.0 \text{mm}$)	Current - Output (Max)	3.54A
Polarization Positive Center Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Power (Watts)	85W
Applications ITE (Commercial), Medical Efficiency Level VI, CoC Tier 2 Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	No Load Power Consumption	150mW (Max)
Efficiency Level VI, CoC Tier 2 Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.31^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.46^{\circ}\text{H} (135.0 \text{mm} \times 37.0 \text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.31^{\circ}\text{L} \times 2.44^{\circ}\text{W} \times 1.46^{\circ}\text{H} (135.0\text{mm} \times 37.0\text{mm})$	Applications	ITE (Commercial), Medical
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Efficiency	Level VI, CoC Tier 2
Size / Dimension 5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.31" L x 2.44" W x 1.46" H (135.0mm x 62.0mm x 37.0mm)
		Report errors?

ALM85US24C2-8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALM85US24C2-8 Payment Methods



















ALM85US24C2-8 Shipping Methods













If you have any question about ALM85US24C2-8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com