



ALS70G334NP040 Information

Heisener.com

Part Number ALS70G334NP040

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330000UF 20% 40V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALS70G334NP040 Specifications

Manufacturer Part Number AL\$70G334NP040 Manufacturer KEMET Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series AL\$70 Capacitance 330000µF Tolerance ±20% Voltage - Rated 40 V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Report errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries ALS70 Capacitance 330000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	ALS70G334NP040
Package Radial, Can - Screw Terminals Series ALS70 Capacitance 330000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS70Capacitance330000µFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency31A @ 100HzRipple Current - High Frequency32.1A @ 10kHzImpedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.031" Dia (77.00mm)Height - Seated (Max)5.827" (148.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series ALS70 Capacitance 330000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 330000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	ALS70
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 31A @ 100Hz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	330000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	40V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 32.1A @ 100Hz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	8 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31A @ 100Hz Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency 32.1A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.031" Dia (77.00mm)Height - Seated (Max)5.827" (148.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	31A @ 100Hz
Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	32.1A @ 10kHz
Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	9 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.031" Dia (77.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.827" (148.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
report errors.		Report errors?

ALS70G334NP040 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS70G334NP040 Payment Methods



















ALS70G334NP040 Shipping Methods













If you have any question about ALS70G334NP040, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com