



# ALS70H103QH350 Information

Heisener.com

Part Number ALS70H103QH350

Manufacturer KEMET Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 10000UF 20% 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ALS70H103QH350 Specifications**

Manufacturer Part Number         ALS70H103QH350           Manufacturer         KEMET           Category         Capacitors           Package         Radial, Can - Screw Terminals           Series         ALS70           Capacitance         10000µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         24 mOhm @ 100Hz           Lifetime @ Temp,         5000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         19.1A @ 100Hz           Ripple Current - High Frequency         26.3A @ 10kHz           Impedance         1.252" (31.80mm)           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.543" Dia (90.00mm)           Height - Seated (Max)         3.93" (100.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series ALS70 Capacitance 10000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency 19.1A @ 100Hz Ripple Current - High Frequency 17 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 1.252" (31.80mm) Size / Dimension 1.252" (31.90mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	ALS70H103QH350
PackageRadial, Can - Screw TerminalsSeriesALS70Capacitance10000µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.1A @ 100HzRipple Current - High Frequency26.3A @ 10kHzImpedance17 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS70Capacitance10000μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.1A @ 100HzRipple Current - High Frequency26.3A @ 10kHzImpedance17 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         ALS70           Capacitance         10000µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         24 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         19.1A @ 100Hz           Ripple Current - High Frequency         26.3A @ 10kHz           Impedance         17 mOhms           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.543" Dia (90.00mm)           Height - Seated (Max)         3.937" (100.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         10000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         24 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         19.1A @ 100Hz           Ripple Current - High Frequency         26.3A @ 10kHz           Impedance         17 mOhms           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.543" Dia (90.00mm)           Height - Seated (Max)         3.937" (100.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz  Lifetime @ Temp. 5000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 19.1A @ 100Hz  Ripple Current - High Frequency 26.3A @ 10kHz  Impedance 17 mOhms  Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 3.937" (100.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	ALS70
Voltage - Rated350VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency19.1A @ 100HzRipple Current - High Frequency26.3A @ 10kHzImpedance17 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	10000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  19.1A @ 100Hz  Ripple Current - High Frequency  19.1A @ 100Hz  Ripple Current - High Frequency  17 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  3.937" (100.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  5000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  19.1A @ 100Hz  Ripple Current - High Frequency  17 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	350V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 26.3A @ 10kHz Impedance 17 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	24 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 19.1A @ 100Hz  Ripple Current - High Frequency 26.3A @ 10kHz  Impedance 17 mOhms  Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 3.937" (100.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 19.1A @ 100Hz Ripple Current - High Frequency 26.3A @ 10kHz Impedance 17 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  26.3A @ 10kHz  Impedance  17 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  3.937" (100.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency  26.3A @ 10kHz  Impedance  17 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.543" Dia (90.00mm)  Height - Seated (Max)  3.937" (100.00mm)  Surface Mount Land Size  -  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Applications	General Purpose
Impedance17 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	19.1A @ 100Hz
Lead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	26.3A @ 10kHz
Size / Dimension 3.543" Dia (90.00mm)  Height - Seated (Max) 3.937" (100.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	17 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.543" Dia (90.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.937" (100.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

### ALS70H103QH350 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ALS70H103QH350 Payment Methods



















## ALS70H103QH350 Shipping Methods













If you have any question about ALS70H103QH350, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com