



ALS70H134KE025 Information

Heisener.com

Part Number ALS70H134KE025

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 130000UF 20% 25V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALS70H134KE025 Specifications

Manufacturer Part Number ALS70H134KE025 Manufacturer KEMET Category Capacitors Package Radial, Can - Screw Terminals Series ALS70 Capacitance 130000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.30" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries ALS70 Capacitance 130000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	ALS70H134KE025
Package Radial, Can - Screw Terminals Series ALS70 Capacitance 130000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS70Capacitance130000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)17 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17.5A @ 100HzRipple Current - High Frequency18.5A @ 10kHzImpedance16 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series ALS70 Capacitance 13000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 130000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	ALS70
Voltage - Rated25VESR (Equivalent Series Resistance)17 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency17.5A @ 100HzRipple Current - High Frequency18.5A @ 10kHzImpedance16 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	130000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 50.874" (22.20mm) Size / Dimension 40.08" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 502.20mm Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Curre	ESR (Equivalent Series Resistance)	17 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 17.5A @ 100Hz Ripple Current - High Frequency 18.5A @ 10kHz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 18.5A @ 100Hz Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 16 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance16 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	17.5A @ 100Hz
Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	18.5A @ 10kHz
Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	16 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.008" Dia (51.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.307" (84.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

ALS70H134KE025 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS70H134KE025 Payment Methods





















ALS70H134KE025 Shipping Methods













If you have any question about ALS70H134KE025, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com