



ALS70H334QH040 Information

Heisener.com

Part Number ALS70H334QH040

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330000UF 20% 40V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALS70H334QH040 Specifications

Manufacturer Part Number ALS70H334QH040 Manufacturer KEMET Category Capacitors Package Radial, Can - Screw Terminals Series ALS70 Capacitance 330000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)		
Category Capacitors Package Radial, Can - Screw Terminals Series ALS70 Capacitance 33000µF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Manufacturer Part Number	ALS70H334QH040
PackageAduninum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesALS70Capacitance330000μFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency31.6A @ 100HzRipple Current - High Frequency32.7A @ 10kHzImpedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS70Capacitance330000μFTolerance±20%Voltage - Rated40VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency31.6A @ 100HzRipple Current - High Frequency32.7A @ 10kHzImpedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)	Category	Capacitors
Series ALS70 Capacitance 330000μF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)		Aluminum Electrolytic Capacitors
Capacitance 330000μF Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 40V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Series	ALS70
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) 3.937" (100.00mm)	Capacitance	330000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) 3.937" (100.00mm)	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Voltage - Rated	40V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 31.6A @ 100Hz Ripple Current - High Frequency 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3-40°C ~ 85°C Polarization 9 mOhrs 31.6A @ 100Hz 32.7A @ 10kHz 9 mOhms 1.252" (31.80mm)	ESR (Equivalent Series Resistance)	8 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 31.6A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 31.6A @ 100Hz 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 31.6A @ 100Hz 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 31.6A @ 100Hz 32.7A @ 10kHz 9 mOhms 1.252" (31.80mm) 3.543" (100.00mm)	Polarization	Polar
Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Applications	General Purpose
Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Ripple Current - Low Frequency	31.6A @ 100Hz
Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Ripple Current - High Frequency	32.7A @ 10kHz
Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm)	Impedance	9 mOhms
Height - Seated (Max) 3.937" (100.00mm)	Lead Spacing	1.252" (31.80mm)
•	Size / Dimension	3.543" Dia (90.00mm)
	Height - Seated (Max)	3.937" (100.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

ALS70H334QH040 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS70H334QH040 Payment Methods





















ALS70H334QH040 Shipping Methods













If you have any question about ALS70H334QH040, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com