



ALS70P914NS025 Information

Heisener.com

Part Number ALS70P914NS025

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 910000UF 20% 25V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









Manufacturer Part Number Manufacturer Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series ALS70 Capacitance 910000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications ALS70 6 mChm @ 100Hz 100H	*	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesALS70Capacitance $910000\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance) $6 \text{ mOhm @ } 100\text{Hz}$ Lifetime @ Temp. $5000 \text{ Hrs @ } 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Manufacturer Part Number	ALS70P914NS025
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series ALS70 Capacitance 910000μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS70Capacitance910000μFTolerance $\pm 20\%$ Voltage - Rated25VESR (Equivalent Series Resistance)6 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature -40 °C ~ 85 °CPolarizationPolarApplicationsGeneral Purpose	Category	Capacitors
SeriesALS70Capacitance910000μFTolerance $\pm 20\%$ Voltage - Rated25VESR (Equivalent Series Resistance)6 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature -40 °C ~ 85 °CPolarizationPolarApplicationsGeneral Purpose		Aluminum Electrolytic Capacitors
Capacitance910000μFTolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance) $6 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $5000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Package	Radial, Can - Screw Terminals
Tolerance $\pm 20\%$ Voltage - Rated $25V$ ESR (Equivalent Series Resistance) $6 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $5000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Polarization Polar Applications General Purpose	Series	ALS70
Voltage - Rated $25V$ ESR (Equivalent Series Resistance) $6 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $5000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Capacitance	910000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose	Tolerance	±20%
Lifetime @ Temp. $5000 \text{Hrs} @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose	ESR (Equivalent Series Resistance)	6 mOhm @ 100Hz
Polarization Polar Applications General Purpose	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose	Operating Temperature	-40°C ~ 85°C
•	Polarization	Polar
D' 1 C 1 F	Applications	General Purpose
Ripple Current - Low Frequency 34.3A @ 100Hz	Ripple Current - Low Frequency	34.3A @ 100Hz
Ripple Current - High Frequency 34.8A @ 10kHz	Ripple Current - High Frequency	34.8A @ 10kHz
Impedance 8 mOhms	Impedance	8 mOhms
Lead Spacing 1.252" (31.80mm)	Lead Spacing	1.252" (31.80mm)
Size / Dimension 3.031" Dia (77.00mm)	Size / Dimension	3.031" Dia (77.00mm)
Height - Seated (Max) 7.717" (196.00mm)	Height - Seated (Max)	7.717" (196.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

ALS70P914NS025 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS70P914NS025 Payment Methods



















ALS70P914NS025 Shipping Methods













If you have any question about ALS70P914NS025, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com