



ALS71A564QH025 Information

Heisener.com

Part Number ALS71A564QH025

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 560000UF 20% 25V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALS71A564QH025 Specifications

Manufacturer Part Number ALS71A564QH025 Manufacturer KEMET Category Capacitors Package Radial, Can - Screw Terminals Series ALS71 Capacitance 560000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 32.A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Tille Vigitoze Specifications	
Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Screw Terminals Series ALS71 Capacitance 560000µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) ESR (Equivalent Series Resistance) Soud Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Size / Dimension Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Radial, Can - Screw Terminals Radial, Can - Screw Terminals ALS71 Capacitors Radial, Can - Screw Terminals ALS71 50000µF ±20% **COPACITATION OF TOP	Manufacturer Part Number	ALS71A564QH025
PackageRadial, Can - Screw TerminalsSeriesALS71Capacitance560000μFTolerance±20%Voltage - Rated25 VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency32.7 @ 100HzRipple Current - High Frequency32.7 @ 10kHzImpedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS71Capacitance560000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency32A @ 100HzRipple Current - High Frequency32.7A @ 10kHzImpedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-	Category	Capacitors
Series ALS71 Capacitance 560000μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 32A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 560000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 32A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 32A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Series	ALS71
Voltage - Rated ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 32A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size -	Capacitance	560000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 32.7A @ 100Hz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 32A @ 100Hz Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar Polar -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -	ESR (Equivalent Series Resistance)	8 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size -	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 32.7A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Applications	General Purpose
Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	32A @ 100Hz
Lead Spacing 1.252" (31.80mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 3.937" (100.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	32.7A @ 10kHz
Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)3.937" (100.00mm)Surface Mount Land Size-	Impedance	9 mOhms
Height - Seated (Max) Surface Mount Land Size 3.937" (100.00mm) -	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size -	Size / Dimension	3.543" Dia (90.00mm)
	Height - Seated (Max)	3.937" (100.00mm)
Mounting Type Chassis Mount	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

ALS71A564QH025 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS71A564QH025 Payment Methods



















ALS71A564QH025 Shipping Methods













If you have any question about ALS71A564QH025, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com