

ALS71H332KF350

Request a Quote

ALS71H332KF350 Information

	Part Number	ALS71H332KF350
Heisener.com	Manufacturer	KEMET
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 3300UF 20% 350V SCREW
	Package	Radial, Can - Screw Terminals
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ALS71H332KF350 Specifications

Manufacturer KEMET Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series ALS71 Capacitance 3300µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 59 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 16.2A @ 10kHz Impedance 36 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.213" (107.00mm) Surface Mount Land Size - Mounting Type Chasis Mount Package / Case Kadial, Can - Screw Terminals	-	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series ALS71 Capacitance 3300µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 59 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.7A @ 100Hz Impedance 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.213" (107.00mm) Surface Mount Land Size - Mounting Type Chasis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	ALS71H332KF350
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsPackageALS71Capacitance3300µFTolerance±20%Voltage - Rated500ESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature6000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency612 A @ 100HzRipple Current - High Frequency616 A @ 100HzImpedance36 mOhmsLad Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKadial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS71Capacitance3300μFTolerance±20%Voltage - Rated50 VESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency9.7A @ 100HzRiple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874° (22.20mm)Size / Dimension4.213° (107.00mm)Height - Seated (Max)4.213° (107.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Screw Terminals	Category	Capacitors
SeriesALS71Capacitance3300µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension4.213" (107.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance3300µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Pokage / CaseRadial, Can - Screw Terminals	Series	ALS71
Voltage - Rated350VESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Screw Terminals	Capacitance	3300µF
ESR (Equivalent Series Resistance)59 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzBipple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)-Nurface Mount Land Size-Package / CaseRadial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzRipple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension4.213" (107.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Voltage - Rated	350V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzRipple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	59 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzRipple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lifetime @ Temp.	5000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency9.7A @ 100HzRipple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency9.7A @ 100HzRipple Current - High Frequency16.2A @ 10kHzImpedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance36 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	9.7A @ 100Hz
Lead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	16.2A @ 10kHz
Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Impedance	36 mOhms
Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Size / Dimension	2.008" Dia (51.00mm)
Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Height - Seated (Max)	4.213" (107.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

ALS71H332KF350 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS71H332KF350 Payment Methods





If you have any question about ALS71H332KF350, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com