



#### **ALS81G564NP025 Information**

Heisener.com

Part Number ALS81G564NP025

Manufacturer KEMET Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 560000UF 20% 25V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ALS81G564NP025 Specifications**

Manufacturer Part Number         ALS81G564NP025           Manufacturer         KEMET           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         ALS81           Capacitance         560000µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         8 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         26.8A @ 100Hz           Ripple Current - High Frequency         27.5A @ 10kHz           Impedance         9 mOhms           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.031" Dia (77.00mm)           Height - Seated (Max)         5.827" (148.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Repart errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries ALS81 Capacitance 560000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 27.5A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	ALS81G564NP025
Aluminum Electrolytic Capacitors  Package Radial, Can - Screw Terminals  Series ALS81  Capacitance 560000µF  Tolerance ±20%  Voltage - Rated 25V  ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz  Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 26.8A @ 100Hz  Ripple Current - High Frequency 27.5A @ 10kHz  Impedance 9 mOhms  Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.031" Dia (77.00mm)  Height - Seated (Max) 5.827" (148.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS81Capacitance560000µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)8 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency26.8A @ 100HzRipple Current - High Frequency27.5A @ 10kHzImpedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.031" Dia (77.00mm)Height - Seated (Max)5.827" (148.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         ALS81           Capacitance         560000µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         8 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         26.8A @ 100Hz           Ripple Current - High Frequency         27.5A @ 10kHz           Impedance         9 mOhms           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.031" Dia (77.00mm)           Height - Seated (Max)         5.827" (148.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         560000µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         8 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         26.8A @ 100Hz           Ripple Current - High Frequency         27.5A @ 10kHz           Impedance         9 mOhms           Lead Spacing         1.252" (31.80mm)           Size / Dimension         3.031" Dia (77.00mm)           Height - Seated (Max)         5.827" (148.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 25V  ESR (Equivalent Series Resistance) 8 mOhm @ 100Hz  Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 26.8A @ 100Hz  Ripple Current - High Frequency 27.5A @ 10kHz  Impedance 9 mOhms  Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.031" Dia (77.00mm)  Height - Seated (Max) 5.827" (148.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	ALS81
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  27.5A @ 10kHz  Impedance  9 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Rmindment	Capacitance	560000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  26.8A @ 100Hz  Ripple Current - High Frequency  27.5A @ 10kHz  Impedance  9 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.031" Dia (77.00mm)  Height - Seated (Max)  5.827" (148.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  26.8A @ 100Hz  Ripple Current - High Frequency  27.5A @ 10kHz  Impedance  9 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.031" Dia (77.00mm)  Height - Seated (Max)  5.827" (148.00mm)  Surface Mount Land Size  -  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	25V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 26.8A @ 100Hz Ripple Current - High Frequency 27.5A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	8 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 26.8A @ 100Hz Ripple Current - High Frequency 27.5A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 26.8A @ 100Hz Ripple Current - High Frequency 27.5A @ 10kHz Impedance 9 mOhms Lead Spacing 1.252" (31.80mm) Size / Dimension 3.031" Dia (77.00mm) Height - Seated (Max) 5.827" (148.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  27.5A @ 10kHz  Impedance  9 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.031" Dia (77.00mm)  Height - Seated (Max)  5.827" (148.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency  27.5A @ 10kHz  Impedance  9 mOhms  Lead Spacing  1.252" (31.80mm)  Size / Dimension  3.031" Dia (77.00mm)  Height - Seated (Max)  5.827" (148.00mm)  Surface Mount Land Size  -  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Applications	General Purpose
Impedance9 mOhmsLead Spacing1.252" (31.80mm)Size / Dimension3.031" Dia (77.00mm)Height - Seated (Max)5.827" (148.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	26.8A @ 100Hz
Lead Spacing 1.252" (31.80mm)  Size / Dimension 3.031" Dia (77.00mm)  Height - Seated (Max) 5.827" (148.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	27.5A @ 10kHz
Size / Dimension 3.031" Dia (77.00mm)  Height - Seated (Max) 5.827" (148.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	9 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.031" Dia (77.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.827" (148.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
Report crists:		Report errors?

#### **ALS81G564NP025 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ALS81G564NP025 Payment Methods**





















## **ALS81G564NP025 Shipping Methods**













If you have any question about ALS81G564NP025, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com