



ALS81H202DE200 Information

Heisener.com

Part Number ALS81H202DE200

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2000UF 20% 200V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALS81H202DE200 Specifications

Manufacturer Part Number ALS81H202DE200 Manufacturer KEMET Category Capacitors Package Radial, Can - Screw Terminals Series ALS81 Capacitance 2000µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 131 mOhm @ 100Hz Lifetime @ Temp, 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	*	
CategoryCapacitorsPackageRadial, Can - Screw TerminalsScriesALS81Capacitance2000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)131 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8 A @ 100HzRipple Current - High Frequency9.1 A @ 10kHzImpedance89 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	ALS81H202DE200
Package Radial, Can - Screw Terminals Series ALS81 Capacitance 2000μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 131 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS81Capacitance2000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)131 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency9.1A @ 10kHzImpedance89 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series ALS81 Capacitance 2000μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 131 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 2000µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 131 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 131 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Size / Dimension 1.417" Dia (36.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	ALS81
Voltage - Rated200VESR (Equivalent Series Resistance)131 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency9.1A @ 10kHzImpedance89 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	2000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Size / Dimension Cize / Dimension Ripple Current Size / Dimension Cize / D	ESR (Equivalent Series Resistance)	131 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 4.8A @ 100Hz Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size	Polarization	Polar
Ripple Current - High Frequency 9.1A @ 10kHz Impedance 89 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance89 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.417" Dia (36.00mm)Height - Seated (Max)3.307" (84.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	4.8A @ 100Hz
Lead Spacing 0.504" (12.80mm) Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	9.1A @ 10kHz
Size / Dimension 1.417" Dia (36.00mm) Height - Seated (Max) 3.307" (84.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	89 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.504" (12.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.417" Dia (36.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.307" (84.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

ALS81H202DE200 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALS81H202DE200 Payment Methods



















ALS81H202DE200 Shipping Methods













If you have any question about ALS81H202DE200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com