



### ALS81H202KF450 Information

Heisener.com

Part Number ALS81H202KF450

Manufacturer KEMET Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 2000UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ALS81H202KF450 Specifications**

Manufacturer Part Number         ALS81H202KF450           Manufacturer         KEMET           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         ALS81           Capacitance         2000µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         85 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         General Purpose           Ripple Current - Low Frequency         7.3A @ 100Hz           Ripple Current - High Frequency         13.9A @ 10kHz           Impedance         54 mOhms           Lead Spacing         0.874" (22.20mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.213" (107.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	•	
CategoryCapacitorsPackageRadial, Can - Screw TerminalsScriesALS81Capacitance2000µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7.3A @ 100HzRipple Current - High Frequency13.9A @ 10kHzImpedance54 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	ALS81H202KF450
Package         Radial, Can - Screw Terminals           Series         ALS81           Capacitance         2000μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         85 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         7.3A @ 100Hz           Ripple Current - High Frequency         13.9A @ 10kHz           Impedance         54 mOhms           Lead Spacing         0.874" (22.20mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.213" (107.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	KEMET
PackageRadial, Can - Screw TerminalsSeriesALS81Capacitance2000µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7.3A @ 100HzRipple Current - High Frequency13.9A @ 10kHzImpedance54 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         ALS81           Capacitance         2000μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         85 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         7.3A @ 100Hz           Ripple Current - High Frequency         13.9A @ 10kHz           Impedance         54 mOhms           Lead Spacing         0.874" (22.20mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.213" (107.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         2000µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         85 mOhm @ 100Hz           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         7.3A @ 100Hz           Ripple Current - High Frequency         13.9A @ 10kHz           Impedance         54 mOhms           Lead Spacing         0.874" (22.20mm)           Size / Dimension         2.008" Dia (51.00mm)           Height - Seated (Max)         4.213" (107.00mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 450V  ESR (Equivalent Series Resistance) 85 mOhm @ 100Hz  Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 7.3A @ 100Hz  Ripple Current - High Frequency 13.9A @ 10kHz  Impedance 54 mOhms  Lead Spacing 0.874" (22.20mm)  Size / Dimension 2.008" Dia (51.00mm)  Height - Seated (Max) 4.213" (107.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	ALS81
Voltage - Rated450 VESR (Equivalent Series Resistance)85 mOhm @ 100 HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7.3A @ 100 HzRipple Current - High Frequency13.9A @ 10kHzImpedance54 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	2000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  7.3A @ 100Hz  Ripple Current - High Frequency  13.9A @ 10kHz  Impedance  54 mOhms  Lead Spacing  0.874" (22.20mm)  Size / Dimension  4.213" (107.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  7.3A @ 100Hz  Ripple Current - High Frequency  13.9A @ 10kHz  Impedance  54 mOhms  Lead Spacing  0.874" (22.20mm)  Size / Dimension  4.213" (107.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	450V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 13.9A @ 10kHz Impedance 54 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.213" (107.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	85 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency 7.3A @ 100Hz Ripple Current - High Frequency 13.9A @ 10kHz Impedance 54 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.213" (107.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 7.3A @ 100Hz Ripple Current - High Frequency 13.9A @ 10kHz Impedance 54 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.213" (107.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  13.9A @ 10kHz  Impedance  54 mOhms  Lead Spacing  0.874" (22.20mm)  Size / Dimension  2.008" Dia (51.00mm)  Height - Seated (Max)  4.213" (107.00mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 54 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.008" Dia (51.00mm) Height - Seated (Max) 4.213" (107.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance54 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.008" Dia (51.00mm)Height - Seated (Max)4.213" (107.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	7.3A @ 100Hz
Lead Spacing 0.874" (22.20mm)  Size / Dimension 2.008" Dia (51.00mm)  Height - Seated (Max) 4.213" (107.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	13.9A @ 10kHz
Size / Dimension 2.008" Dia (51.00mm)  Height - Seated (Max) 4.213" (107.00mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	54 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.008" Dia (51.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.213" (107.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

### ALS81H202KF450 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ALS81H202KF450 Payment Methods





















## ALS81H202KF450 Shipping Methods













If you have any question about ALS81H202KF450, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com