



ALZ12B05 Information



For Reference Only

Part Number ALZ12B05

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 16A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ALZ12B05 Specifications

Manufacturer Part NumberALZ12B05ManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesALZRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough Hole		
CategoryRelaysPackage-SeriesALZRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - Fully	Manufacturer Part Number	ALZ12B05
Package - Series ALZ Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Manufacturer	Panasonic Electric Works
Package - Series ALZ Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Category	Relays
SeriesALZRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage440VAC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesInsulation - Class B, Sealed - Fully		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Package	-
Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Series	ALZ
Coil Current 80mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 440VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Coil Current	80mA
Contact Rating (Current) Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Coil Voltage	5VDC
Switching Voltage 440VAC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Switching Voltage	440VAC - Max
Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Fully	Turn On Voltage (Max)	3.5 VDC
Release Time 5ms Features Insulation - Class B, Sealed - Fully	Turn Off Voltage (Min)	0.5 VDC
Features Insulation - Class B, Sealed - Fully	Operate Time	15ms
·	Release Time	5ms
Mounting Type Through Hole	Features	Insulation - Class B, Sealed - Fully
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

ALZ12B05 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ALZ12B05 Payment Methods



















ALZ12B05 Shipping Methods













If you have any question about ALZ12B05, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com