



AM2520SURCK09 Information

Part Number AM2520SURCK09

Manufacturer Kingbright

Category Optoelectronics

LED Indication - Discrete

DescriptionLED RED CLEAR 2SMD REVPackage2-SMD, Z-Bend, Bottom Entry

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AM2520SURCK09 Specifications

Manufacturer Part Number AM2520SURCK09 Manufacturer Kingbright Category Optoelectronics LED Indication - Discrete Package 2-SMD, Z-Bend, Bottom Entry Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1000mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645mm Features - Supplier Device Package 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	•	
Category Optoelectronics LED Indication - Discrete Package 2-SMD, Z-Bend, Bottom Entry Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1000mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Manufacturer Part Number	AM2520SURCK09
Package 2-SMD, Z-Bend, Bottom Entry Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1000mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Manufacturer	Kingbright
Package 2-SMD, Z-Bend, Bottom Entry Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1000mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Category	Optoelectronics
Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1000mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95 V Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm		LED Indication - Discrete
Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 1000mcd Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Package	2-SMD, Z-Bend, Bottom Entry
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating1000mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.95VCurrent - Test20mAViewing Angle20°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nmWavelength - Peak645nmFeatures-Package / Case2-SMD, Z-Bend, Bottom EntrySupplier Device Package2-SMD, Z-BendSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.90mm	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating1000mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.95VCurrent - Test20mAViewing Angle20°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nmWavelength - Peak645nmFeatures-Package / Case2-SMD, Z-Bend, Bottom EntrySupplier Device Package2-SMD, Z-BendSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.90mm	Color	Red
Lens TransparencyClearMillicandela Rating1000mcdLens Style/SizeRound with Domed Top, 1.90mmVoltage - Forward (Vf) (Typ)1.95VCurrent - Test20mAViewing Angle20°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nmWavelength - Peak645nmFeatures-Package / Case2-SMD, Z-Bend, Bottom EntrySupplier Device Package2-SMD, Z-BendSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.90mm	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95 V Current - Test 20mA Viewing Angle Voiewing Angle Surface Mount, Bottom Entry Wavelength - Dominant Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package Size / Dimension Lens Style/Size Round with Domed 1.90mm 1.95 V 20mA 20° Surface Mount, Bottom Entry 630nm 645nm 645nm 645nm 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Lens Color	Colorless
Lens Style/Size Round with Domed Top, 1.90mm Voltage - Forward (Vf) (Typ) 1.95V Current - Test 20mA Viewing Angle Voward (Vf) (Typ) Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package Size / Dimension L x 2.00mm W Height (Max) 20mA	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package Size / Dimension Height (Max) 1.95V 20mA 20° Surface Mount, Bottom Entry 630nm 630nm 645nm 645nm 7 2-SMD, Z-Bend, Bottom Entry 2-SMD, Z-Bend 3.50mm L x 2.00mm W 2.90mm	Millicandela Rating	1000mcd
Current - Test 20mA Viewing Angle 20° Mounting Type Surface Mount, Bottom Entry Wavelength - Dominant 630nm Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Lens Style/Size	Round with Domed Top, 1.90mm
Viewing Angle20°Mounting TypeSurface Mount, Bottom EntryWavelength - Dominant630nmWavelength - Peak645nmFeatures-Package / Case2-SMD, Z-Bend, Bottom EntrySupplier Device Package2-SMD, Z-BendSize / Dimension2.50mm L x 2.00mm WHeight (Max)2.90mm	Voltage - Forward (Vf) (Typ)	1.95V
Mounting Type Surface Mount, Bottom Entry 630nm Wavelength - Dominant 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Current - Test	20mA
Wavelength - Dominant Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Viewing Angle	20°
Wavelength - Peak 645nm Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Mounting Type	Surface Mount, Bottom Entry
Features - Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Wavelength - Dominant	630nm
Package / Case 2-SMD, Z-Bend, Bottom Entry Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Wavelength - Peak	645nm
Supplier Device Package 2-SMD, Z-Bend Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Features	-
Size / Dimension 2.50mm L x 2.00mm W Height (Max) 2.90mm	Package / Case	2-SMD, Z-Bend, Bottom Entry
Height (Max) 2.90mm	Supplier Device Package	2-SMD, Z-Bend
	Size / Dimension	2.50mm L x 2.00mm W
Report errors?	Height (Max)	2.90mm
		Report errors?

AM2520SURCK09 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AM2520SURCK09 Payment Methods

































If you have any question about AM2520SURCK09, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com