



## **AMC06DRSZ Information**

Heisener.com

Part Number AMC06DRSZ

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 12POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AMCOCDDCZ	C
AMC06DRSZ	Specifications

Manufacturer Part Number       AMC06DRSZ         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       6         Number of Positions       12         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30µin (0.76µm)         Contact Type       Loop Bellows         Color       -         Flange Feature       Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 150°C	MVICOODKSZ Specifications		
Category Cand Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features  Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color - Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature - 65° C ~ 150° C	Manufacturer Part Number	AMC06DRSZ	
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         6           Number of Positions         12           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Beryllium Copper           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Loop Bellows           Color         -           Flange Feature         Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color - Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	6	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	12	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features  Mounting Type  Through Hole  Termination  Solder  Contact Material  Beryllium Copper  Contact Finish  Contact Finish Thickness  30μin (0.76μm)  Contact Type  Loop Bellows  Color  Flange Feature  Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness $30\mu$ in $(0.76\mu$ m)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, $0.125$ " ( $3.18$ mm) DiaOperating Temperature $-65$ °C ~ $150$ °C	Pitch	0.100" (2.54mm)	
Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 30μin (0.76μm)  Contact Type Loop Bellows  Color -  Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Features	-	
Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows  Color -  Flange Feature Flush Mount, Side Opening, Unthreaded, $0.125$ " ( $3.18mm$ ) Dia  Operating Temperature $-65$ °C $\sim 150$ °C	Mounting Type	Through Hole	
Contact Finish Gold Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows Color - Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Termination	Solder	
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Loop Bellows Color - Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Contact Material	Beryllium Copper	
Contact Type Loop Bellows  Color -  Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 150°C	Contact Finish	Gold	
Color - Flange Feature Flush Mount, Side Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 150$ °C	Contact Finish Thickness	30μin (0.76μm)	
Flange Feature Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	-	
	Flange Feature	Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia	
Donort among	Operating Temperature	-65°C ~ 150°C	
Report errors a			Report errors?

#### **AMC06DRSZ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **AMC06DRSZ Payment Methods**



















# **AMC06DRSZ Shipping Methods**













If you have any question about AMC06DRSZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com