

AMC22DRAI

AMC22DRAI Information

Heisener.com	 AMC22DRAI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 44POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AMC22DRAI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull SectureContact TypeFull BellowsContact TypeFull BellowsContact TypeFull SectureContact TypeTop Mount Opening, Threaded Insert, 4-40	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Manufacturer Part Number	AMC22DRAI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature-50°C ~ 150°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeGreenFlange Feature-Operating Temperature-Solder-Contact FinishSolderContact TypeSolderContact Type-Solder-Contact Type-Solder-Contact Type-Solder-Contact Type-Solder-Contact Type-Solder-ColorGreenFlange Feature-Operating Temperature-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder-Solder<		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessSoljari (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Package	-
GenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeGoldContact TypeFull BellowsColorGreenFlange Feature-Operating Temperature-Operating Temperature-	Series	-
Number of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 150°C	Card Type	Non Specified - Dual Edge
Number of Positions 44 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Gold Contact Finish Thickness Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 150°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	22
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Number of Positions	44
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-55°C ~ 150°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Termination	Solder
Contact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Finish	Gold
ColorGreenFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 150°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 150°C
		Report errors ⁶

AMC22DRAI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AMC22DRAI Payment Methods



AMC22DRAI Shipping Methods



If you have any question about AMC22DRAI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com