



AMC24DRMD Information

Heisener.com

Part Number AMC24DRMD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 48POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AMC24DRMD Specifications

Manufacturer Part Number AMC24DRMD Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color -	*	
Category Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Hounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Type Loop Bellows Card Edge Connectors - Edgeboard Connectors - Amounting Type Beryllium Copper Contact Type Loop Bellows	Manufacturer Part Number	AMC24DRMD
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 24 Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows	Package	-
GenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop Bellows	Series	-
Number of Positions/Bay/Row 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows	Card Type	Non Specified - Dual Edge
Number of Positions 48 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows	Gender	Female
Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop Bellows	Number of Positions/Bay/Row	24
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop Bellows	Number of Positions	48
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop Bellows	Card Thickness	0.093" (2.36mm)
Features - Mounting Type Through Hole Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows	Number of Rows	2
Mounting TypeThrough HoleTerminationWire WrapContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop Bellows	Pitch	0.100" (2.54mm)
Termination Wire Wrap Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows	Features	-
Contact Material Beryllium Copper Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows	Termination	Wire Wrap
Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows	Contact Material	Beryllium Copper
Contact Type Loop Bellows	Contact Finish	Gold
	Contact Finish Thickness	30μin (0.76μm)
Color -	Contact Type	Loop Bellows
	Color	-
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Operating Temperature	-65°C ~ 150°C
Report errors?		Report errors?

AMC24DRMD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AMC24DRMD Payment Methods



















AMC24DRMD Shipping Methods













If you have any question about AMC24DRMD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com