

AML27ABK2BA22BC

AML27ABK2BA22BC Information

Part Number AML27ABK2BA22BC

Manufacturer Honeywell Sensing and Productivity Solutions

Category Switches

Keylock Switches

Description SWITCH KEY 2POS SPDT 100MA 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AML27ABK2BA22BC Specifications

Manufacturer Part Number AML27ABK2BA22BC Manufacturer Honeywell Sensing and Productivity Solutions Category Switches Package - Series AML27 Circuit SPDT Number of Positions 2 Switch Function On-On Contact Timing Not Specified Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -		
Category Switches Package - Series AML27 Circuit SPDT Number of Positions 2 Switch Function On-On Contact Timing Not Specified Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Manufacturer Part Number	AML27ABK2BA22BC
Keylock Switches Package - Series AML27 Circuit SPDT Number of Positions 2 Switch Function On-On Contact Timing Not Specified Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package - Series AML27 Circuit SPDT Number of Positions 2 Switch Function On-On Contact Timing Not Specified Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Category	Switches
SeriesAML27CircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating100mA (AC/DC)Voltage Rating - AC125VVoltage Rating - DC125VActuator TypeFlat KeyKey Removable PositionsAllAngle of Throw90°Contact Material-Contact FinishGoldMounting TypePanel Mount, Snap-InTermination StyleSolder, Quick Connect - 0.110" (2.8mm)Panel Cutout DimensionsSquare - 19.05mm²Features-		Keylock Switches
CircuitSPDTNumber of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating $100mA (AC/DC)$ Voltage Rating - AC $125V$ Voltage Rating - DC $125V$ Actuator TypeFlat KeyKey Removable PositionsAllAngle of Throw 90° Contact Material-Contact FinishGoldMounting TypePanel Mount, Snap-InTermination StyleSolder, Quick Connect - 0.110° ($2.8mm$)Panel Cutout DimensionsSquare - $19.05mm^2$ Features-	Package	-
Number of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating100mA (AC/DC)Voltage Rating - AC125 VVoltage Rating - DC125 VActuator TypeFlat KeyKey Removable PositionsAllAngle of Throw90°Contact Material-Contact FinishGoldMounting TypePanel Mount, Snap-InTermination StyleSolder, Quick Connect - 0.110" (2.8mm)Panel Cutout DimensionsSquare - 19.05mm²Features-	Series	AML27
Switch Function On-On Contact Timing Not Specified Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Circuit	SPDT
Contact Timing Not Specified Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Number of Positions	2
Current Rating 100mA (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Switch Function	On-On
Voltage Rating - AC Voltage Rating - DC 125V Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Features - 125V 12	Contact Timing	Not Specified
Voltage Rating - DC Actuator Type Flat Key Key Removable Positions All Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Current Rating	100mA (AC/DC)
Actuator Type Key Removable Positions All Angle of Throw Contact Material Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Voltage Rating - AC	125V
Key Removable PositionsAllAngle of Throw90°Contact Material-Contact FinishGoldMounting TypePanel Mount, Snap-InTermination StyleSolder, Quick Connect - 0.110" (2.8mm)Panel Cutout DimensionsSquare - 19.05mm²Features-	Voltage Rating - DC	125V
Angle of Throw 90° Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Actuator Type	Flat Key
Contact Material - Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Key Removable Positions	All
Contact Finish Gold Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Angle of Throw	90°
Mounting Type Panel Mount, Snap-In Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm² Features -	Contact Material	-
Termination Style Solder, Quick Connect - 0.110" (2.8mm) Panel Cutout Dimensions Square - 19.05mm ² Features -	Contact Finish	Gold
Panel Cutout Dimensions Square - 19.05mm ² Features -	Mounting Type	Panel Mount, Snap-In
Features -	Termination Style	Solder, Quick Connect - 0.110" (2.8mm)
	Panel Cutout Dimensions	Square - 19.05mm ²
Report errors?	Features	-
		Report errors?

AML27ABK2BA22BC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AML27ABK2BA22BC Payment Methods



















AML27ABK2BA22BC Shipping Methods













If you have any question about AML27ABK2BA22BC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com