



# **AMM08DRUH Information**

Heisener.com

Part Number AMM08DRUH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 16POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **AMM08DRUH Specifications**

Manufacturer Part Number       AMM08DRUH         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       8         Number of Positions       16         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 150°C	Minimobical Specifications	
Category Cannectors, Interconnects Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	AMM08DRUH
Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects
Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       8         Number of Positions       16         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card Type Gender Female  Number of Positions/Bay/Row 8 Number of Positions 16 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Through Hole Termination Solder Contact Material Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Color Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Package	-
Gender Female  Number of Positions/Bay/Row 8  Number of Positions 16  Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.156" (3.96mm)  Features - Mounting Type Through Hole  Termination Solder  Contact Material Beryllium Copper  Contact Finish Gold  Contact Finish Thickness 30µin (0.76µm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-
Number of Positions       8         Number of Positions       16         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	8
Number of Rows       2         Pitch       0.156" (3.96mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Beryllium Copper         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       Green         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	16
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.156" (3.96mm)
Termination  Solder  Contact Material  Beryllium Copper  Contact Finish  Gold  Contact Finish Thickness  30μin (0.76μm)  Contact Type  Full Bellows  Color  Green  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder
Contact Finish Thickness 30μin (0.76μm)  Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Beryllium Copper
Contact Type Full Bellows  Color Green  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
Color Green Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Full Bellows
	Color	Green
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
	Operating Temperature	-65°C ~ 150°C
Report errors		Report errors?

### **AMM08DRUH Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **AMM08DRUH Payment Methods**



















## **AMM08DRUH Shipping Methods**













If you have any question about AMM08DRUH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com