

# AMM12DTBS-S189

#### AMM12DTBS-S189 Information

Heisener.com	 AMM12DTBS-S189 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 24POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **AMM12DTBS-S189 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Type0.602° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeSolderContact Finish ThicknessSolderContact Finish ThicknessSoldin CopperContact TypeGoldContact TypeSolin (0.76µm)Contact TypeSolin (0.76µm)Contact Finish ThicknessSolin (0.76µm)Contact TypeSolin (0.76	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions/Bay/Row24Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsContact TypeGodContact TypeSolderContact TypeSolin (0.76µm)Contact TypeSolin (0.76µm)Contact TypeGodContact TypeSolin (0.76µm)Contact TypeSide Mount Opening, Unthreaded, 0.125″ (3.18mm) DiaColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125″ (3.18mm) DiaOperating Temperature-55°C ~150°C	Manufacturer Part Number	AMM12DTBS-S189	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact TypeIop BellowsContact TypeGoldContact TypeGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperatureo.5°C ~ 150°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeGoldContact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Series	-	
Number of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeJour (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 150°C	Card Type	Non Specified - Dual Edge	
Number of Positions 24   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole, Right Angle   Cortact Material Solder   Contact Finish Gold   Contact Finish Thickness 30µin (0.76µm)   Cortact Type Loop Bellows   Color Green   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 150°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions/Bay/Row	12	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	24	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-55°C ~ 150°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Features	-	
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Termination	Solder	
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper	
Contact TypeLoop BellowsColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish	Gold	
ColorGreenFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 150°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Color	Green	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	$-65^{\circ}C \sim 150^{\circ}C$	
			Report errors?

#### **AMM12DTBS-S189 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### AMM12DTBS-S189 Payment Methods





If you have any question about AMM12DTBS-S189, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com