

AMM25DREF

lest a Quote

AMM25DREF Information

	Part Number	AMM25DREF	
	Manufacturer	Sullins Connector Solutions	
(A Heisener.com	Category	 AMM25DREF Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 50POS 0.156 - For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com 	
Constanting cantery	Description	CONN EDGE DUAL FMALE 50POS 0.156	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AMM25DREF Specifications

ManufacturerSullins Connector SolutionsCardegoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions/Bay/Row0602° (1.57mm)Number of Rows0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeSolder Eyelet(s)Contact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeGuld (0.76µm)Contact TypeFull BellowsContact TypeGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-50°C				
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypePanel MountContact FinishSolder Eyelt(s)Contact Finish ThicknessGoldContact Finish ThicknessGuin (0.76µm)Contact TypeFull BellowsContact TypeSolid Solid	Manufacturer Part Number	AMM25DREF		
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Manufacturer	Sullins Connector Solutions		
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorGreenFlange Feature- Sol°C ~ 150°C	Category	Connectors, Interconnects		
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeGreenFlange Feature-Operating Temperature-65°C ~ 150°C		Card Edge Connectors - Edgeboard Connectors		
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature65°C ~ 150°C	Package	-		
GenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Series	-		
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Card Type	Non Specified - Dual Edge		
Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Gold Contact Finish Gold Contact Type Full Bellows Color Green Flange Feature Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia Operating Temperature -65°C ~ 150°C	Gender	Female		
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-55°C ~ 150°C	Number of Positions/Bay/Row	25		
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialGoldContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Positions	50		
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Card Thickness	0.062" (1.57mm)		
Features-Mounting TypePanel MountMounting TypeSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Number of Rows	2		
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Pitch	0.156" (3.96mm)		
TerminationSolder Eyelet(s)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Features	-		
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Mounting Type	Panel Mount		
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Termination	Solder Eyelet(s)		
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Material	Beryllium Copper		
Contact TypeFull BellowsColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish	Gold		
ColorGreenFlange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Finish Thickness	30µin (0.76µm)		
Flange FeatureTop Mount Opening, Floating Bobbin, 0.116" (2.95mm) DiaOperating Temperature-65°C ~ 150°C	Contact Type	Full Bellows		
Operating Temperature $-65^{\circ}C \sim 150^{\circ}C$	Color	Green		
	Flange Feature	Top Mount Opening, Floating Bobbin, 0.116" (2.95mm) Dia		
Report errors?	Operating Temperature	$-65^{\circ}C \sim 150^{\circ}C$		
			Report errors?	

AMM25DREF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AMM25DREF Payment Methods



AMM25DREF Shipping Methods



If you have any question about AMM25DREF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com