



AMM31DTMD Information

Heisener.com

Part Number AMM31DTMD

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 62POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AMM31DTMD Specifications

Manufacturer Part Number AMM31DTMD Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 150°C	Ministrations Specifications	
Card Edge Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Package Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	AMM31DTMD
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card Type	Package	-
Gender Female Number of Positions/Bay/Row 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Series	-
Number of Positions 31 Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions 62 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	31
Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	62
Pitch 0.156" (3.96mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColorGreenFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.156" (3.96mm)
Termination Solder Contact Material Beryllium Copper Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact Material Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Beryllium Copper Gold Contact Type Loop Bellows Color Green Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle
Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder
Contact Finish Thickness 30μin (0.76μm) Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Beryllium Copper
Contact Type Loop Bellows Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
Color Green Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Loop Bellows
	Color	Green
Operating Temperature -65°C ~ 150°C	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia
	Operating Temperature	-65°C ~ 150°C
Report errors		Report errors?

AMM31DTMD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AMM31DTMD Payment Methods



















AMM31DTMD Shipping Methods













If you have any question about AMM31DTMD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com