



APE3004H Information

NAIS www.hitls@jjer.com

For Reference Only

Part Number APE3004H

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 6A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









APE3004H Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Power Relays, Over 2 Amps Package - Series APE Relay Type General Purpose Coil Type Non Latching Coil Current 38mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Release Time Ams Features Mounting Type Through Hole Termination Style Perport arrors Parts Amps Perport arrors Parts Amps		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesAPERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38mACoil Voltage4.5 VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)2.97 VDCTurn Off Voltage (Min)0.225 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	APE3004H
Package - Series APE Relay Type General Purpose Coil Type Non Latching Coil Current 38mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style Purpose APE APE APE APE APE APE APE APE APE AP	Manufacturer	Panasonic Electric Works
Package - Series APE Relay Type General Purpose Coil Type Non Latching Coil Current 38mA Coil Voltage 4.5 VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesAPERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38mACoil Voltage4.5 VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)2.97 VDCTurn Off Voltage (Min)0.225 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current38mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - MaxTurn On Voltage (Max)2.97 VDCTurn Off Voltage (Min)0.225 VDCOperate Time8msRelease Time4msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Non Latching Coil Current 38mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features Mounting Type Through Hole Termination Style PC Pin	Series	APE
Coil Current 38mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	38mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	4.5VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 2.97 VDC Turn Off Voltage (Min) 0.225 VDC Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 8ms Release Time 4ms Features Mounting Type Through Hole Termination Style 2.97 VDC 3.225 VDC 4ms Termination Style 2.97 VDC 5.25 VDC 5.25 VDC 7.26 VDC 7.27 VDC 7.27 VDC 7.28 VDC 8ms 7.28 VDC 8ms 7.28 VDC 8ms 7.28 VDC 8ms PC Pin	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style O.225 VDC Through Hole PC Pin	Switching Voltage	250VAC - Max
Operate Time 8ms Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	2.97 VDC
Release Time 4ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.225 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	8ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	-
·	Mounting Type	Through Hole
Panort arrors?	Termination Style	PC Pin
Report errors:		Report errors?

APE3004H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

APE3004H Payment Methods



















APE3004H Shipping Methods













If you have any question about APE3004H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com