

APTD3216SRCPRV

APTD3216SRCPRV Information



For Reference Only

Part Number APTD3216SRCPRV

Manufacturer Kingbright
Category Optoelectronics

LED Indication - Discrete

Description LED RED CLEAR 1206 SMD

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









APTD3216SRCPRV Specifications

Manufacturer Part Number APTD3216SRCPRV Manufacturer Kingbright Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 150mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W Height (Max) 1.87mm	•	
Category Optoelectronics LED Indication - Discrete Package 1206 (3216 Metric) Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 150mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Manufacturer Part Number	APTD3216SRCPRV
Package 1206 (3216 Metric) Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 150mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Manufacturer	Kingbright
Package 1206 (3216 Metric) Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 150mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Category	Optoelectronics
Series - Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 150mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W		LED Indication - Discrete
Color Red Configuration - Lens Color Colorless Lens Transparency Clear Millicandela Rating 150mcd Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Package	1206 (3216 Metric)
Configuration-Lens ColorColorlessLens TransparencyClearMillicandela Rating150medLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)1.85VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant640nmWavelength - Peak655nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Series	-
Lens ColorColorlessLens TransparencyClearMillicandela Rating150mcdLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)1.85VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant640nmWavelength - Peak655nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Color	Red
Lens TransparencyClearMillicandela Rating150mcdLens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)1.85VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant640nmWavelength - Peak655nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Configuration	-
Millicandela Rating Lens Style/Size Round with Domed Top, 1.60mm Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 350mm L x 1.60mm W	Lens Color	Colorless
Lens Style/SizeRound with Domed Top, 1.60mmVoltage - Forward (Vf) (Typ)1.85VCurrent - Test20mAViewing Angle35°Mounting TypeSurface MountWavelength - Dominant640nmWavelength - Peak655nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Lens Transparency	Clear
Voltage - Forward (Vf) (Typ) 1.85V Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package Size / Dimension 1.85V 20mA 35° Surface Mount 640nm 640nm 635nm Features - Package / Case 1206 (3216 Metric) 3.20mm L x 1.60mm W	Millicandela Rating	150mcd
Current - Test 20mA Viewing Angle 35° Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Lens Style/Size	Round with Domed Top, 1.60mm
Viewing Angle35°Mounting TypeSurface MountWavelength - Dominant640nmWavelength - Peak655nmFeatures-Package / Case1206 (3216 Metric)Supplier Device Package2-SMDSize / Dimension3.20mm L x 1.60mm W	Voltage - Forward (Vf) (Typ)	1.85V
Mounting Type Surface Mount Wavelength - Dominant 640nm Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Current - Test	20mA
Wavelength - Dominant Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Viewing Angle	35°
Wavelength - Peak 655nm Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Mounting Type	Surface Mount
Features - Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Wavelength - Dominant	640nm
Package / Case 1206 (3216 Metric) Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Wavelength - Peak	655nm
Supplier Device Package 2-SMD Size / Dimension 3.20mm L x 1.60mm W	Features	-
Size / Dimension 3.20mm L x 1.60mm W	Package / Case	1206 (3216 Metric)
	Supplier Device Package	2-SMD
Height (Max) 1.87mm	Size / Dimension	3.20mm L x 1.60mm W
	Height (Max)	1.87mm
Report errors?		Report errors?

APTD3216SRCPRV Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

APTD3216SRCPRV Payment Methods



















APTD3216SRCPRV Shipping Methods













If you have any question about APTD3216SRCPRV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com