

# AQ12EM750JAJME

# **AQ12EM750JAJME Information**



**Part Number** AQ12EM750JAJME **Manufacturer** AVX Corporation

**Category** Capacitors

Ceramic Capacitors

**Description** CAP CER 75PF 150V 0606

**Package** 0606 (1616 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **AQ12EM750JAJME Specifications**

Manufacturer Part Number         AQ12EM750JAJME           Manufacturer         AVX Corporation           Category         Capacitors           Package         0606 (1616 Metric)           Series         AQ           Capacitance         75pF           Tolerance         ±5%           Voltage - Rated         150V           Temperature Coefficient         M           Operating Temperature         -55°C ~ 175°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0606 (1616 Metric)           Size / Dimension         0.055" L x 0.055" W (1.40mm x 1.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.057" (1.45mm)           Lead Spacing         -		
Category         Capacitors           Package         0606 (1616 Metric)           Series         AQ           Capacitance         75pF           Tolerance         ±5%           Voltage - Rated         150V           Temperature Coefficient         M           Operating Temperature         -55°C ~ 175°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0606 (1616 Metric)           Size / Dimension         0.055" L x 0.055" W (1.40mm x 1.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.057" (1.45mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	AQ12EM750JAJME
Package         0606 (1616 Metric)           Series         AQ           Capacitance         75pF           Tolerance         ±5%           Voltage - Rated         150V           Temperature Coefficient         M           Operating Temperature         -55°C ~ 175°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0606 (1616 Metric)           Size / Dimension         0.055" L x 0.055" W (1.40mm x 1.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.057" (1.45mm)           Lead Spacing         -           Lead Style         -	Manufacturer	AVX Corporation
Package         0606 (1616 Metric)           Series         AQ           Capacitance         75pF           Tolerance         ±5%           Voltage - Rated         150V           Temperature Coefficient         M           Operating Temperature         -55°C ~ 175°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0606 (1616 Metric)           Size / Dimension         0.055" L x 0.055" W (1.40mm x 1.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.057" (1.45mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         AQ           Capacitance         75pF           Tolerance         ±5%           Voltage - Rated         150V           Temperature Coefficient         M           Operating Temperature         -55°C ~ 175°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0606 (1616 Metric)           Size / Dimension         0.055" L x 0.055" W (1.40mm x 1.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.057" (1.45mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         75pF           Tolerance         ±5%           Voltage - Rated         150V           Temperature Coefficient         M           Operating Temperature         -55°C ~ 175°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0606 (1616 Metric)           Size / Dimension         0.055" L x 0.055" W (1.40mm x 1.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.057" (1.45mm)           Lead Spacing         -           Lead Style         -	Package	0606 (1616 Metric)
Tolerance ±5%  Voltage - Rated 150V  Temperature Coefficient M  Operating Temperature -55°C ~ 175°C  Features High Q, Low Loss  Ratings -  Applications RF, Microwave, High Frequency  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 0606 (1616 Metric)  Size / Dimension 0.055" L x 0.055" W (1.40mm x 1.40mm)  Height - Seated (Max) -  Thickness (Max) 0.057" (1.45mm)  Lead Spacing -  Lead Style -	Series	AQ
Voltage - Rated150VTemperature CoefficientMOperating Temperature-55°C ~ 175°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0606 (1616 Metric)Size / Dimension0.055" L x 0.055" W (1.40mm x 1.40mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Capacitance	75pF
Temperature Coefficient Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0606 (1616 Metric) Size / Dimension 0.055" L x 0.055" W (1.40mm x 1.40mm) Height - Seated (Max) Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Tolerance	±5%
Operating Temperature-55°C ~ 175°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0606 (1616 Metric)Size / Dimension0.055" L x 0.055" W (1.40mm x 1.40mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Voltage - Rated	150V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0606 (1616 Metric)Size / Dimension0.055" L x 0.055" W (1.40mm x 1.40mm)Height - Seated (Max)-Thickness (Max)0.057" (1.45mm)Lead Spacing-Lead Style-	Temperature Coefficient	M
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0606 (1616 Metric) Size / Dimension 0.055" L x 0.055" W (1.40mm x 1.40mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style - One of the surface of the surfa	Operating Temperature	-55°C ~ 175°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0606 (1616 Metric) Size / Dimension 0.055" L x 0.055" W (1.40mm x 1.40mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0606 (1616 Metric) Size / Dimension 0.055" L x 0.055" W (1.40mm x 1.40mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0606 (1616 Metric) Size / Dimension 0.055" L x 0.055" W (1.40mm x 1.40mm) Height - Seated (Max) - Thickness (Max) 0.057" (1.45mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case       0606 (1616 Metric)         Size / Dimension       0.055" L x 0.055" W (1.40mm x 1.40mm)         Height - Seated (Max)       -         Thickness (Max)       0.057" (1.45mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.055" L x 0.055" W (1.40mm x 1.40mm)         Height - Seated (Max)       -         Thickness (Max)       0.057" (1.45mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0606 (1616 Metric)
Thickness (Max) 0.057" (1.45mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.055" L x 0.055" W (1.40mm x 1.40mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.057" (1.45mm)
·	Lead Spacing	-
Domont among	Lead Style	-
Report errors?		Report errors?

## **AQ12EM750JAJME Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **AQ12EM750JAJME Payment Methods**



















#### **AQ12EM750JAJME Shipping Methods**













If you have any question about AQ12EM750JAJME, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com