

AQ137M6R8BA1ME

AQ137M6R8BA1ME Information



For Reference Only

Part Number AQ137M6R8BA1ME Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 6.8PF 500V 1111

Package 1111 (2828 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AQ137M6R8BA1ME Specifications

Manufacturer Part Number AQ137M6R8BAIME Manufacturer AVX Corporation Category Capacitors Package 1111 (2828 Metric) Series AQ Capacitance 6.8pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q. Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -		
Category Capacitors Package 1111 (2828 Metric) Series AQ Capacitance 6.8pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Manufacturer Part Number	AQ137M6R8BA1ME
Package 1111 (2828 Metric) Series AQ Capacitance 6.8pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Manufacturer	AVX Corporation
Package 1111 (2828 Metric) Series AQ Capacitance 6.8pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Category	Capacitors
Series AQ Capacitance 6.8pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -		Ceramic Capacitors
Capacitance 6.8pF Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Package	1111 (2828 Metric)
Tolerance ±0.1pF Voltage - Rated 500V Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Series	AQ
Voltage - Rated Temperature Coefficient M Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension Height - Seated (Max) - Thickness (Max) Lead Spacing 500V M 0.100" (2.59mm) Lead Spacing	Capacitance	6.8pF
Temperature Coefficient Operating Temperature -55°C ~ 175°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Tolerance	±0.1pF
Operating Temperature-55°C ~ 175°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1111 (2828 Metric)Size / Dimension0.110" L x 0.110" W (2.79mm x 2.79mm)Height - Seated (Max)-Thickness (Max)0.102" (2.59mm)Lead Spacing-	Voltage - Rated	500V
FeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1111 (2828 Metric)Size / Dimension0.110" L x 0.110" W (2.79mm x 2.79mm)Height - Seated (Max)-Thickness (Max)0.102" (2.59mm)Lead Spacing-	Temperature Coefficient	M
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Operating Temperature	-55°C ~ 175°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Applications	RF, Microwave, High Frequency
Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.102" (2.59mm) -	Package / Case	1111 (2828 Metric)
Thickness (Max) 0.102" (2.59mm) Lead Spacing -	Size / Dimension	0.110" L x 0.110" W (2.79mm x 2.79mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.102" (2.59mm)
Lead Style	Lead Spacing	-
Lead Style	Lead Style	-
Report errors?		Report errors?

AQ137M6R8BA1ME Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AQ137M6R8BA1ME Payment Methods



















AQ137M6R8BA1ME Shipping Methods













If you have any question about AQ137M6R8BA1ME, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com