

AQ15A-050A Information



For Reference Only

Part Number AQ15A-050A Manufacturer Phihong USA

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC WALL MOUNT ADAPTER 5V 15W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









AQ15A-050A Specifications

Manufacturer Part Number AQ15A-050A Manufacturer Phihong USA Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AQ15 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series AQ15 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Manufacturer Part Number	AQ15A-050A
Package - Series AQ15 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Manufacturer	Phihong USA
Package - Series AQ15 Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesAQ15Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input90 ~ 264 VACVoltage - Output5VCurrent - Output (Max)3APower (Watts)15WNo Load Power Consumption75mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorUSB C ReceptacleSize / Dimension2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $3A$ Power (Watts) $15W$ No Load Power Consumption $75mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorUSB C ReceptacleSize / Dimension 2.05 " L x 1.57 " W x 0.92 " H $(52.0mm$ x $40.0mm$ x $23.3mm$)	Package	-
FormWall MountInput TypeFixed BladeVoltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output $5V$ Current - Output (Max) $3A$ Power (Watts) $15W$ No Load Power Consumption $75mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorUSB C ReceptacleSize / Dimension 2.05° L x 1.57° W x 0.92° H $(52.0mm$ x $40.0mm$ x $23.3mm$)	Series	AQ15
Input Type Fixed Blade Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 5V Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade Fixed Blade For ~ 264 VAC	Region Utilized	North America
Voltage - Input 90 ~ 264 VAC Voltage - Output 5V Current - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 90 ~ 264 VAC 5V Current - Output (Max) 15W 15W 15W 15W 15W 15W 15W 15	Form	Wall Mount
Voltage - Output (Max) 3A Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Input Type	Fixed Blade
Current - Output (Max) Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 3A 15W 15W 15W 15W 15W 15W 15W 15	Voltage - Input	90 ~ 264 VAC
Power (Watts) 15W No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 15W 75mW (Max) - Level VI 0°C ~ 40°C USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Voltage - Output	5V
No Load Power Consumption 75mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Current - Output (Max)	3A
Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Power (Watts)	15W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	No Load Power Consumption	75mW (Max)
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector USB C Receptacle Size / Dimension $2.05^{\circ}\text{L x } 1.57^{\circ}\text{W x } 0.92^{\circ}\text{H } (52.0\text{mm x } 40.0\text{mm x } 23.3\text{mm})$	Applications	ITE (Commercial)
Output Connector USB C Receptacle Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Efficiency	Level VI
Size / Dimension 2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	USB C Receptacle
Report errors?	Size / Dimension	2.05" L x 1.57" W x 0.92" H (52.0mm x 40.0mm x 23.3mm)
		Report errors?

AQ15A-050A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

AQ15A-050A Payment Methods



















AQ15A-050A Shipping Methods













If you have any question about AQ15A-050A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com