

AR 16 HZL/01-TT

AR 16 HZL/01-TT Information

	 AR 16 HZL/01-TT Assmann WSW Components Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 16POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AR 16 HZL/01-TT Specifications

ManufacturerAssmann WSW ComponentsCategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Finish Thickness - MatingBeryllium CopperContact Material - MatingSolderPitch - PostOpen FrameTerminationSolderPitch - PostTinContact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - PostBeryllium CopperHousing MaterialHernplastic, PolyesterOperating Temperature-40°C ~ 105°C		
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series-SpeeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating10µin (0.25µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish F. Post20µin (5.08µm)Contact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - Post20µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThremoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Manufacturer Part Number	AR 16 HZL/01-TT
Sockets for ICs, TransistorsPackage-Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Finish Thickness - MatingDeer FrameMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBeryllium CopperHousing MaterialMaterialOperating Temperature40°C ~ 105°C	Manufacturer	Assmann WSW Components
Package-Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish Thickness - PostBeryllium CopperContact Finish Thickness - PostBeryllium CopperContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Material - PostSolderContact Material - PostSolderContact Material - PostHormoplastic, PolyesterHousing MaterialThermoplastic, PolyesterOperating Temperature40°C ~ 105°C	Category	Connectors, Interconnects
Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeBeryllium CopperFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature40°C ~ 105°C		Sockets for ICs, Transistors
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - Post200µin (5.08µm)Contact Material - PostBeryllium CopperContact Material - Post200µin (5.08µm)Contact Material - PostBeryllium CopperContact Material - Post200µin (5.08µm)Contact Material - PostHorespectContact Material - Post40°C ~ 105°C	Package	-
Number of Positions or Pins (Grid)16 (2 x 8)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Series	-
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Туре	DIP, 0.3" (7.62mm) Row Spacing
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostThermoplastic, PolyesterOperating Temperature40°C ~ 105°C	Number of Positions or Pins (Grid)	16 (2 x 8)
Contact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Pitch - Mating	0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostContact Finish - PostContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish Thickness - Mating	10µin (0.25µm)
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBeryllium CopperContact Material - PostThermoplastic, PolyesterHousing Material-40°C ~ 105°C	Contact Material - Mating	Beryllium Copper
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Mounting Type	Through Hole
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Features	Open Frame
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Pitch - Post	0.100" (2.54mm)
Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish - Post	Tin
Housing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish Thickness - Post	200µin (5.08µm)
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material - Post	Beryllium Copper
	Housing Material	Thermoplastic, Polyester
Report errors?	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
		Report errors?

AR 16 HZL/01-TT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AR 16 HZL/01-TT Payment Methods



AR 16 HZL/01-TT Shipping Methods



If you have any question about AR 16 HZL/01-TT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com