

AR 18-HZW/TN

Request a Quote

AR 18-HZW/TN Information

TATAT	Part Number	AR 18-HZW/TN	
THE OWNER OF THE OWNER	Manufacturer	Assmann WSW Components	- F
Ween Remener.com	Category	Connectors, Interconnects Sockets for ICs, Transistors	
	Description	CONN IC DIP SOCKET 18POS GOLD	l K
	Package	-	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



AR 18-HZW/TN Specifications

Manufacturer Part NumberAR 18-HZW/TNManufacturerAssmann WSW ComponentsCategoryConnectors, InterconnectsPackage-Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - MatingGoldContact Finish - MatingGoldContact Finish Thickness - Mating-FacturesOpen FrameFocturesOpen FrameForturesJino" (2.54mm)FocturesOpen FrameFocturesOpen FrameForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)FocturesOpen FrameForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesSockets ForturesForturesDip (3.50kpm)ForturesDip (3.50kpm)ForturesSockets ForturesForturesSockets F		
CategoryConnectors, InterconnectsBackage-Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationVire WrapPitch - PostInContact Finish - PostDino" (2.54mm)Contact Finish - PostOpen FrameTerminationWire WrapPitch - Post10.00" (2.54mm)Contact Finish - PostDino" (2.54mm)Contact Finish - PostDino" (2.54mm)Contact Finish - PostDino" (2.54mm)Contact Finish - PostSoupin (2.54mm)Contact Finish - PostSoupin (2.54mm)Contact Finish - PostSoupin (2.54mm)Contact Finish - PostSoupin (2.54mm)Contact Finish - PostTinContact Finish Thickness - PostSoupin (5.08µm)Contact Finish Thickness - PostSoupin (5.08µm)Contact Finish Thickness - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterHousing Temperature-40°C ~ 105°C	Manufacturer Part Number	AR 18-HZW/TN
NumberSockets for ICs, TransistorsPackage-Series-TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating-Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFreminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Fortart Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish Thickness - PostSoljuin (5.08µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostHermoplastic, PolyesterForenting Temperature-40°C ~ 105°C	Manufacturer	Assmann WSW Components
Package-Series-TypeDIP, 0.3" (7.62mm Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeMough HoleFeaturesOpen FrameFeatures0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)<	Category	Connectors, Interconnects
Series-TypeDIP, 0.3" (7.62mn) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - PostSini (100 multime)Contact Finish - Post0.100" (2.54mm)Fontact Finish - PostSini (100 multime)Contact Finish - PostSini (100 multime)Contact Finish - PostSini (100 multime)Contact Finish Thickness - PostSini (100 multime)Contact Finish Thickness - PostSini (100 multime)Contact Material - PostSini (100 multime)<		Sockets for ICs, Transistors
TypeDIP, 0.3" (7.62mm) Row SpacingTypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating-Contact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Pitch - Post0.100" (2.54mm)Contact Finish Thickness - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSilpi (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Housing Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Package	-
Number of Positions or Pins (Grid)18 (2 x 9)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBeryllium CopperHousing Material - PostThrough HoleContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostHousing CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Series	-
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Туре	DIP, 0.3" (7.62mm) Row Spacing
Contact Finish - MatingGoldContact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFreminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post20µin (5.08µm)Contact Finish - PostBeryllium CopperHousing Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Number of Positions or Pins (Grid)	18 (2 x 9)
Contact Finish Thickness - Mating-Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-	Pitch - Mating	0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature40°C ~ 105°C	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish Thickness - Mating	-
FeaturesOpen FrameTerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Material - Mating	Beryllium Copper
TerminationWire WrapPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Mounting Type	Through Hole
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Features	Open Frame
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Termination	Wire Wrap
Contact Finish Thickness - Post200μin (5.08μm)Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Pitch - Post	0.100" (2.54mm)
Contact Material - PostBeryllium CopperHousing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish - Post	Tin
Housing MaterialThermoplastic, PolyesterOperating Temperature-40°C ~ 105°C	Contact Finish Thickness - Post	200µin (5.08µm)
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Material - Post	Beryllium Copper
	Housing Material	Thermoplastic, Polyester
	Operating Temperature	-40°C ~ 105°C
Report errors		Report errors?

AR 18-HZW/TN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

AR 18-HZW/TN Payment Methods



AR 18-HZW/TN Shipping Methods



If you have any question about AR 18-HZW/TN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com