

ARJ11B-MASAS-LU2

ARJ11B-MASAS-LU2 Information



For Reference Only

Part Number ARJ11B-MASAS-LU2

Manufacturer Abracon LLC

Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 100 BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARJ11B-MASAS-LU2 Specifications

Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series ARJ11B Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Number of Cores per Jack 4 Shielding Shielded, EMI Finger		
Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series ARJ11B Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Contact Material - Contact Material Operating Temperature O°C ~ 70°C	Manufacturer Part Number	ARJ11B-MASAS-LU2
Modular Connectors - Jacks With Magnetics Package - Series ARJ11B Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Manufacturer	Abracon LLC
Package - Series ARJ11B Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Category	Connectors, Interconnects
SeriesARJ11BConnector TypeRJ45Number of Ports1Number of Rows1Applications10/100 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionDownContact Material-Contact FinishGoldOperating Temperature0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector Type Number of Ports 1 Number of Rows 1 Applications 10/100 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Package	-
Number of Ports1Number of Rows1Applications10/100 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionDownContact Material-Contact FinishGoldOperating Temperature0°C ~ 70°C	Series	ARJ11B
Number of Rows1Applications10/100 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.545" (13.84mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionDownContact Material-Contact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board LED Color Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Contact Material Contact Finish Operating Temperature 10/100 Base-T, AutoMDIX Through Hole 10/20 Base-T, AutoMDIX 10/100 Base-T, AutoMDIX 10/100 Base-T, AutoMDIX 10/20 Base-Tate 10/	Number of Ports	1
Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100 Base-T, AutoMDIX
Termination Solder Height Above Board 0.545" (13.84mm) LED Color Does Not Contain LED Number of Cores per Jack 4 Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board LED Color Does Not Contain LED Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material Contact Finish Gold Operating Temperature 0.545" (13.84mm) Does Not Contain LED A Gontact Material Contact Finish Gold Operating Temperature	Orientation	90° Angle (Right)
LED ColorDoes Not Contain LEDNumber of Cores per Jack4ShieldingShielded, EMI FingerFeaturesBoard LockTab DirectionDownContact Material-Contact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 4 Shielded, EMI Finger Board Lock Foat Lock Operating Temperature 4 Shielded, EMI Finger Board Lock Foat Lock Operating Temperature 5 Shielded, EMI Finger Board Lock Foat Lock Operating Temperature 6 Operating Temperature	Height Above Board	0.545" (13.84mm)
Shielding Shielded, EMI Finger Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	LED Color	Does Not Contain LED
Features Board Lock Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	4
Tab Direction Down Contact Material - Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Shielding	Shielded, EMI Finger
Contact Material - Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Features	Board Lock
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Down
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	-
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

ARJ11B-MASAS-LU2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARJ11B-MASAS-LU2 Payment Methods



















ARJ11B-MASAS-LU2 Shipping Methods













If you have any question about ARJ11B-MASAS-LU2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com