

ARJ2212 Information



For Reference Only

Part Number ARJ2212

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF DPDT 300MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARJ2212 Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series ARJ Relay Type RF Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 300mA Switching Voltage 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Mounting Type Through Hole Termination Style Page 1 1 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1		
CategoryRelaysPackage-SeriesARJRelay TypeRFCoil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)300mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	ARJ2212
Package - Series ARJ Relay Type RF Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 300mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Panasonic Electric Works
Package - Series ARJ Relay Type RF Coil Type Latching, Dual Coil Coil Current 12.5mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 300mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesARJRelay TypeRFCoil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)300mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)300mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current12.5mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)300mASwitching Voltage30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	ARJ
Coil Current Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 300mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style 12.5mA 12.5mA 12.5mA 12.5mA 12.5mA 12.5mA 12VDC 5ms 5ms 5ms Through Hole PC Pin	Relay Type	RF
Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) 300mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) 300mA Switching Voltage 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	12.5mA
Contact Rating (Current) Switching Voltage 30VDC - Max Turn On Voltage (Max) 7 Urn Off Voltage (Min) Operate Time Sms Release Time 5 ms Features Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 7 Urn Off Voltage (Min) Operate Time Sms Release Time Sms Features - Mounting Type Through Hole Termination Style 30VDC - Max 9 VDC 5 ms - Through Hole PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9 VDC Turn Off Voltage (Min) Operate Time 5 ms Release Time 5 ms Features - Mounting Type Through Hole Termination Style	Contact Rating (Current)	300mA
Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	30VDC - Max
Operate Time 5ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9 VDC
Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Papart arrors?	Termination Style	PC Pin
Report errors?		Report errors?

ARJ2212 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARJ2212 Payment Methods



















ARJ2212 Shipping Methods













If you have any question about ARJ2212, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com