



ARN12A4H Information

Heisener.com

Part Number ARN12A4H

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

RELAY RF SPDT 4.5V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ARN12A4H Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series ARN Relay Type RF Coil Type Latching, Dual Coil Coil Current 88.9mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Release Time Sealed - Flux Protection Mounting Type Gress Relays Signal Relays Latching Volt 2 Amps - ARN Relay Type 0 2 Latching, Dual Coil ARN Relay Type Latching, Dual Coil Latching, Dual Coil ARN Relay Type Latching, Dual Coil ASYDC Latching, Dual Coil Sease ASYDC - SPDT (1 Form C) - Switching Voltage - Turn On Voltage (Max) - Sims Sealed - Flux Protection Mounting Type Surface Mount Termination Style		
CategoryRelaysPackage-SeriesARNRelay TypeRFCoil TypeLatching, Dual CoilCoil Current88.9mACoil Voltage4.5 VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	ARN12A4H
Package-SeriesARNRelay TypeRFCoil TypeLatching, Dual CoilCoil Current88.9mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeSurface MountTermination StyleGull Wing	Manufacturer	Panasonic Electric Works
Package - Series ARN Relay Type RF Coil Type Latching, Dual Coil Coil Current 88.9mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time Sealed - Flux Protection Mounting Type Surface Mount Termination Style GRAN	Category	Relays
SeriesARNRelay TypeRFCoil TypeLatching, Dual CoilCoil Current88.9mACoil Voltage4.5 VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay Type Coil Type Latching, Dual Coil Coil Current 88.9mA Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time 5ms Release Time 5ms Release Time 5ms Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Package	-
Coil TypeLatching, Dual CoilCoil Current88.9mACoil Voltage4.5VDCContact FormSPDT (1 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeSurface MountTermination StyleGull Wing	Series	ARN
Coil Current Coil Voltage 4.5 VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) Operate Time Sms Release Time Sms Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	RF
Coil Voltage 4.5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style 4.5VDC 4.5VDC SPDT (1 Form C) - SPDT (1 Form C) - Sms Saled - Flux Protection Surface Mount Gull Wing	Coil Type	Latching, Dual Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style SPDT (1 Form C) - SPDT (1 Form C) SPDT (1 Form C) - SPDT (1 Form C) Splay Surface Mount Gull Wing	Coil Current	88.9mA
Contact Rating (Current) Switching Voltage - Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	4.5VDC
Switching Voltage - Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Contact Rating (Current)	-
Turn Off Voltage (Min) Operate Time Sms Release Time Sms Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	-
Operate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	3.38 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	5ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	5ms
Termination Style Gull Wing	Features	Sealed - Flux Protection
	Mounting Type	Surface Mount
	Termination Style	Gull Wing
Report errors?		Report errors?

ARN12A4H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ARN12A4H Payment Methods





















ARN12A4H Shipping Methods













If you have any question about ARN12A4H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com